INFORMATION TO USERS

This manuscript has been reproduced from the microfilm master. UMI films the text directly from the original or copy submitted. Thus, some thesis and dissertation copies are in typewriter face, while others may be from any type of computer printer.

The quality of this reproduction is dependent upon the quality of the copy submitted. Broken or indistinct print, colored or poor quality illustrations and photographs, print bleedthrough, substandard margins, and improper alignment can adversely affect reproduction.

In the unlikely event that the author did not send UMI a complete manuscript and there are missing pages, these will be noted. Also, if unauthorized copyright material had to be removed, a note will indicate the deletion.

Oversize materials (e.g., maps, drawings, charts) are reproduced by sectioning the original, beginning at the upper left-hand corner and continuing from left to right in equal sections with small overlaps.

ProQuest Information and Learning
300 North Zeeb Road, Ann Arbor, MI 48106-1346 USA
800-521-0600

UMI[®]

NOTE TO USERS

This reproduction is the best copy available.

UMI[®]

HEAT TRANSFER IN SPOUTED BEDS

by

M. A. Malek

A thesis submitted in partial fulfillment
of the requirements for the degree of

DOCTOR OF PHILOSOPHY

in the

DEPARTMENT OF CHEMICAL ENGINEERING

UNIVERSITY OF OTTAWA

Ottawa, Canada

March, 1963

Approved by

Ph.D. Candidate

UMI Number: DC52545

INFORMATION TO USERS

The quality of this reproduction is dependent upon the quality of the copy submitted. Broken or indistinct print, colored or poor quality illustrations and photographs, print bleed-through, substandard margins, and improper alignment can adversely affect reproduction.

In the unlikely event that the author did not send a complete manuscript and there are missing pages, these will be noted. Also, if unauthorized copyright material had to be removed, a note will indicate the deletion.

UMI[®]

UMI Microform DC52545
Copyright 2007 by ProQuest LLC
All rights reserved. This microform edition is protected against
unauthorized copying under Title 17, United States Code.

ProQuest LLC
789 East Eisenhower Parkway
P.O. Box 1346
Ann Arbor, MI 48106-1346

ACKNOWLEDGEMENT

Sincere appreciation and thanks are due to Professor Benjamin C.-Y. Lu whose guidance and encouragement are an integral part of this work.

The author thanks Professor L. A. Madonna under whose guidance the work was started.

Thanks are due to Dr. G. L. Osberg and Dr. T.M. Dauphinee of the National Research Council of Canada for their help in many phases of this work; to graduate students, particularly Mrs. K.S.Y. Wu and Mr. G. Campbell for their participation in discussion; and to Messrs. J. Gasperetti and F. Giacobbi for their help in building the apparatus.

The financial aid given by the National Research Council of Canada is gratefully acknowledged.

TABLE OF CONTENTS

	<u>PAGE</u>
LIST OF TABLES	vi
LIST OF FIGURES	vii
ABSTRACT	1
INTRODUCTION	3
LITERATURE SURVEY	6
Packed bed	6
Fluidized bed	9
Spouted bed	12
EXPERIMENTAL	14
General Consideration of Apparatus	14
Column	14
Thermocouples	18
Water system	20
Air system	20
Regeneration of silica gel	21
Operational Procedure	22
Spouted bed	22
Fluidized bed	23
Solid Particles	25
Bulk density	25
Absolute density	25
Particle diameter	27

	<u>PAGE</u>
Shape factor	27
Porosity	27
Thermal Conductivity and Specific Heat	28
Introduction	28
Experimental	29
Theoretical consideration	31
Results	33
Discussion	37
RESULTS	39
FLOW MECHANISM IN SPOUTED BEDS	47
CORRELATION OF DATA	61
Spouted bed	61
Transition bed	67
DISCUSSION OF EXPERIMENTAL RESULTS	73
Temperature measurement and calculation of h_w	73
Heat transfer to column wall	79
Effect of bed height	85
Effect of thermal properties	87
CONCLUSION	89
APPENDIX	
Pressure Drop	91
Introduction	91
Experimental	93
Theoretical and correlation of data	93

	<u>PAGE</u>
Estimation of Spouted Diameter in a Spouted Bed	105
Introduction	105
Experimental	106
Correlation and discussion	106
Nomenclature	113
References	116
Sample Calculation	120
Tables	123-184

LIST OF TABLES

<u>TABLE</u>		<u>PAGE</u>
1	Physical properties of solid materials	26
2	Factors which may affect heat transfer in a spouted bed	61
3	Factors which may affect heat transfer in a transition bed	67
4-10	Temperature distribution in a 6-in. column	123-135
11-17	Heat transfer coefficient and temperature of different sections in a 6-in. column with 3/4-in. orifice and 13-in. bed height	137-143
18-31	Heat transfer coefficient and temperature of different sections in a 6-in. column with 1/2-in. orifice and 18-in., 13-in. and 9-in. bed heights	144-157
32-35	Heat transfer and temperature of different sections in a 6-in. column with 3/8-in. orifice and 18-in., 13-in. and 9-in. bed heights	158-161
36-39	Heat transfer coefficient and temperature of different sections in a 3-in. column with 1/4-in. orifice and 16-in. and 10-in. bed heights	162-165
40-42	Heat transfer coefficient and temperature for fluidized bed in a 6-in. column	166-168
43-50	Temperature distribution across the cylinder during thermal conductivity measurement	169-176
51	Constants for Bessel functions	177
52	Spout diameter data from a 6-in. semicircular column	178
53	Data on spout diameter	179-182
54	Values of x for which $J_0(x) = 0$ and corresponding values of $J_1(x)$	184

LIST OF FIGURES

<u>FIGURE</u>		<u>PAGE</u>
1	Equipment layout	15
2	6-in. section column	16
3	Conductivity measuring apparatus	30
4	Temperature variation with time	34
5	Steady state temperature distribution	35
6	Typical temperature profile for a spouted bed	40
7	Effect of particle diameter on heat transfer coefficient	42
8	Effect of mass velocity on heat transfer coefficient	43
9	Effect of mass velocity on heat transfer coefficient	44
10	Effect of bed height on Nusselt number	45
11	Vertical heat transfer profile	46
12	Pressure drop flow diagram	50
13	Internal spout at point of maximum pressure drop	52
14	Particle flow pattern in a spouted bed	53
15	Heat transfer mechanism and air particle flow	54
16	Effect of bed height on particle velocity at wall	57
17	Effect of modified Reynolds number on modified Nusselt number	63
18	Determination of exponent b in the equation (37)	64
19	Final heat transfer correlation for spouted bed	66

<u>FIGURE</u>		<u>PAGE</u>
20	Determination of exponent b in equation (49)	69
21	Heat transfer correlation for polystyrene, polyethylene and wheat in a transition bed	70
22	Final heat transfer correlation for transition bed	72
23	Typical radial temperature profile in fluidized and spouted bed	76
24	Typical vertical temperature profile in spouted bed	78
25	Effect of mass velocity on heat transfer coefficient	81
26	Effect of particle diameter on h_w in spouted beds and fluidized beds	83
27	Pressure drop of different columns	97
28	Plot of K , proportionality constant, and D_c , column diameter	99
29	Correlation for maximum pressure drop	100
30	Correlation for spouting drop	103
31	Friction factor vs. modified Reynolds number	104
32	Schematic diagram of a spouted bed	109
33	Effect of mass velocity on spout diameter	110
34	Plot of K , proportionality constant, and D_c , column diameter	111
35	D_s experimental vs. D_s calculated	112

ABSTRACT

The transfer of heat from spouted beds to vertical 6-in. and 3-in. columns was investigated. The bed materials consisted of polyethylene, polystyrene, wheat, rice, millet, Timothy seeds and Ottawa sands. The effect of bed temperature, particle diameter, density and heat capacity, bed height, mass velocity of air and orifice diameter were investigated and correlated. The value of the heat transfer coefficient varied from 10-24 Btu/(hr.)(sq.ft.)(°F).

During spouting, the heat transfer coefficient was found to be independent of mass velocity, column diameter and orifice diameter, but increased with particle diameter and heat capacity, and decreased with bed height.

Heat transfer data in the 6-in. column were collected from the transition bed for polyethylene, polystyrene and wheat with a 13-in. bed height, and 3/4-in. orifice diameter and the results were correlated. The heat transfer coefficient was found to increase with increase in mass velocity up to the point of spouting and at a fixed mass velocity it was found to decrease with increase in bed level.

Experiments were also conducted to collect heat transfer data from a fluidized bed in the 6-in. column with wheat as bed material. It was found that the heat transfer coefficient was from 10-66% lower for a spouted bed than for a fluidized bed and the corresponding mass velocity for spouting varied from 35-55% of that required for obtaining the maximum heat transfer in a fluidized bed under similar flow conditions.

A generalized correlation is proposed to estimate the spout diameter in a spouted bed from literature data as well as from the data collected with the aid of a 6-in. and a 4-in. semicircular column.

An attempt is made to predict the pressure drop for the transition bed and the spouted bed.

INTRODUCTION

Solids-gas contacting operations are among the most important and widely encountered in the chemical process industries and many techniques have been designed to cope with a myriad of special and challenging problems. To meet these challenging problems, various techniques such as spray, moving bed, fluidized and spouted bed have been developed. There is no single technique known as yet that is a universally optimum method or even generally suited for all purposes. Fluidization is extensively used in many industries due to its unique characteristics such as uniformity of fluid and temperature distribution within the bed, high heat and mass transfer rates and ease of transfer of solids. But its application is limited to relatively fine particles, as the coarse particles usually larger than $1/8$ in. in size tend to slug when subjected to fluidization (1,2). To overcome this difficulty, Mathur and Gishler (3) developed a new technique called "The Spouted Bed Technique" for effectively handling the coarse particles.

A spouted bed is a composite of a central fluid spout carrying the solids upward, culminating in a fountain at the top, and a downward moving annulus with a countercurrent flow of fluid. Spouting is achieved by passing a stream of fluid through a conical opening. At low fluid velocities, the fluid simply passes upwards through the solid bed without disturbing the particles; with increasing velocities a certain point is reached where stream of solids is raised rapidly as a central core or spout through the bed and moves down the annulus like a moving bed. It

is difficult to keep the spout steady at the centre of the column; sometimes it oscillates around the axis of the column. The diameter of the spout varies slightly from top to bottom of the bed. However, this variation does not follow any general pattern. It may increase, decrease or remain fairly constant along the bed level and in some cases it may flare out to a maximum half way up the bed (4). About 90% of the solids enter the spout in the cone section and the remainder move from a higher level laterally into the spout. The solids concentration in the central spout increases with bed level and at the same time the physical outline of the channel becomes increasingly less distinct.

At the entrance almost all the fluid passes through the central core as there is not enough time for an appreciable lateral distribution over the cross-section of the column. The percentage of the fluid flowing through the spout decreases with bed level and near the top of the bed almost two-thirds of the total fluid flows through the annulus (3).

The spouted bed technique has been used for drying wheat (5,6) and wood chips (7) and for low temperature carbonization (8). No doubt this technique will find its application in many other fields where intimate contact between solids and fluids is essential, as the present investigation and literature data indicate that it serves the same purpose for coarse particles as fluidization does for fine particles.

For theoretical interest as well as practical application, it is of paramount importance to know the flow characteristics, temperature distribution, heat, mass and momentum transfer in a bed. Considerable

amount of work has been done on flow characteristics and pressure drop in spouted beds and the effect of virtually all important variables is known at least in a qualitative sense, but no generalized correlation is available for pressure drop data and no significant progress has been made on heat, mass and momentum transfer in spouted beds. According to Leva (9), "Although the solids movement seems largely understood in a qualitative sense, finalized quantitative correlations are still lacking. The same may also be said about the fluid flow and prediction of fluid distribution over the column cross-section. It may therefore be stated that the spouted bed technique is still largely unexplored and offers interesting research problems."

The present investigation was undertaken to explore the temperature distribution in a spouted bed and to find a generalized correlation for heat transfer coefficients between the wall and the spouted bed by heating the bed internally with the hot air used for spouting. The following variables were considered in the study:

1. Column diameter
2. Particle diameter
3. Particle density
4. Particle specific heat
5. Orifice diameter
6. Bed height
7. Mass velocity of air
8. Temperature of air

It was also decided to collect pressure drop data from the spouted bed concurrently with the heat transfer experiment.

LITERATURE SURVEY

Packed bed

Much work has been carried out dealing with heat transfer in packed beds, both theoretically and experimentally.

Colburn (10) was one of the earliest investigators who measured the heat transfer between packed beds and the container wall. The apparatus used was a 3-inch and a 1-1/4 inch pipe, 4.5 ft. long and steam jacketed. The diameter of bed materials varied from 1 inch to 0.125 inch and mass velocity varied from 0.2 to 2.6 pounds per second per square foot at pressures of from 1 to 6 atmospheres. The experimental results showed that the heat transfer coefficients at the wall for packed beds were approximately 8 times as large as those for empty tubes.

Leva (11) conducted similar types of experiments to obtain heat transfer coefficients at the wall. The coefficients were correlated with Nusselt number as a function of the Reynolds number and particle-to-tube diameter ratio. The resulting equation predicts a maximum coefficient of heat transfer for a ratio of $\frac{D_p}{D_c} = 0.15$. The apparatus used was a 3-inch and a 1/2-inch tube. Further study by Leva (12) with particle-to-tube diameter ratio as high as 0.660 showed that the heat transfer coefficient was much higher than predicted by their earlier correlations. It was found that the tube diameter itself had little effect on the heat transfer coefficients.

Schumacher (13) concluded that packings of various thermal conductivities and diameters had little effect on the heat transfer

between the wall and the gas flowing through the packings. Chu and Storrow (14) found that the thermal conductivity of the solid had little effect in the low Reynolds number but that it did influence the heat transfer in the higher ranges. The packing diameter had little effect on the heat transfer and increasing packing length had a decreasing effect on heat transfer.

Plautz and Johnstone (15) measured the wall heat transfer coefficient in an 8-inch tube packed with 1/2 and 3/4 inch glass spheres. The wall heat transfer coefficient varied with the superficial mass velocity as $h_w = 0.09 G^{0.75}$ and bed height did not show any effect on h_w .

Reported correlations of measured wall heat transfer coefficients due to Coberly and Marshall (16), Hanratty (17) and Calderbank and Pogorski (18) and Quinton and Storrow (19) are as follows:

$$h = 2.95 G^{0.33} \quad (1)$$

$$\frac{h D_p}{K_g} = 0.95 \left(\frac{D_p G}{\mu} \right)^{0.50} \quad (2)$$

$$\frac{h D_p}{K_g} = 3.60 \left(\frac{D_p G}{\mu} \right)^{0.365} \quad (3)$$

$$h = 0.04 G \quad (4)$$

Yagi and Kuni (20) from studies of annular packed beds in which the heat flowed radially, obtained the heat transfer coefficients on the inner tube surface as well as the mean effective thermal conductivities of the bed. They obtained a new correlation of h_w for $Re_m < 600$ by

means of the equation

$$\frac{h_W D_p}{K_g} = \frac{h_W^* D_p}{K_g} + \alpha_W P_r \text{Re}_m \quad (5)$$

where h_W^* = apparent wall film coefficient with motionless fluid
BTU/(hr)(sq.ft.)(°F).

h_W = apparent wall film coefficient of heat transfer BTU/(hr)(sq.ft.)
(°F).

α_W = (mass velocity of fluid flowing near wall surface in packed
bed in the direction of heat transfer) / (superficial mass
velocity of fluid based on sectional area of empty tube in
the direction of fluid flowing).

They postulated a model of heat transfer mechanisms near the
wall surface in the packed beds, and the following mechanisms were assumed
with the real film coefficient of heat transfer on the wall surface caused
only by the true fluid boundary layer at the wall surface.

a. Heat transfer through solid phases.

1. Heat transfer through the thin gas film near the
contact point.
2. Radiant heat transfer from solid surface to solid
surface.

b. Heat transfer in void spaces, independent of fluid flow.

3. Molecular thermal conduction.
4. Radiant heat transfer from void to void.

c. Heat transfer in void spaces dependent on fluid flow.

5. Heat transfer caused by the lateral mixing of the flowing fluid.

6. Heat transfer through the true boundary film.

Fluidized beds

Over the past decade there has been a vast experimental effort devoted to the study of heat transfer phenomena in fluidized beds, particularly to the heat transfer between the bed and a cooling or heating surface therein.

Leva and coworkers (21,22) studied the effect of bed height, solid density, physical properties of the gas phase and particle and vessel diameters on the heat transfer coefficient for fluidized beds of round and sharp sands and Fischer-Tropsch catalysts in the 100-400 mesh size range.

Three correlating equations were presented:

$$h = 0.64 \frac{K}{\mu} G \eta \quad (6)$$

$$h = 0.86 C G \eta \quad (7)$$

and
$$h = 0.35 C G^{1.15} \quad (8)$$

where η is termed the "fluidization efficiency", developed by these authors during previous work on fluidization (23). Equations (6) and (7) derived from theoretical consideration were found more precise than the entirely empirical equation (8). Variations in bed height, concentration of solids, density of solid phase and vessel diameter were found to have

no effect on the heat transfer coefficient. Values ranging from 0.25 to 80 BTU/(hr.)(sq.ft.)(°F) were obtained for the heat transfer coefficient.

Mickley and Trilling (24) reported the heat transfer characteristics of two columns, one heated internally with a vertical heater, and the other heated electrically through the outside wall. The heat was pictured as being transferred by three mechanisms. Conduction through an air film, convection due to the influence of the moving particles and transfer across the layer by the movement of heat carrying solids. It was further believed that the particles localized the temperature gradients to a thin air film at the wall whose effectiveness was reduced by eddies. The final correlations were presented in terms of the following equations

(a) for internally heated beds:

$$h = 0.0433 \left(\frac{\rho_b^2}{d_p^3} \right)^{0.238} \quad (9)$$

(b) for externally heated beds:

$$h = 0.0118 \left(\frac{\rho_b G_o}{d_p^3} \right)^{0.263} \quad (10)$$

Levenspiel and Walton (25) reported on the effect of operating variables and particle size and shape. In the derivation of certain theoretical equations they considered the solid particles as being stationary and arranged in equally spaced idealized horizontal layers. A number of dimensionless equations were presented. Dow and Jakob (26) observed values of h as high as 174 BTU/(hr.)(sq.ft.)(°F) when heating fluidized beds of aerocat, pitch coke and iron particles. According to

their proposed mechanism, a thermal fluid solid layer was assumed next to the wall. The core of the bed interior was largely at thermal equilibrium, with radial temperature gradients virtually non-existent. In the bottom region of the bed there was a region of thermal mixing. The final correlating equation developed by dimensional analysis was

$$\frac{h D_p}{K_g} = 0.55 \left(\frac{D_p}{L}\right)^{0.65} \left(\frac{D_c}{D_p}\right)^{0.17} \left(\frac{(1-\delta) \rho_s C_s}{\delta \rho_g C_g}\right)^{0.25} \left(\frac{D_c G}{\mu}\right)^{0.80} \quad (11)$$

Van Heerden et al (27,28) collected data from a 3.34 in. I.D. brass vessel over a wide range of solid and fluid properties. It was shown that in its heat transfer properties the fluidized bed was equivalent to a well-stirred liquid, in which the interstitial gas only served as a stirring agent and as a heat transferring medium between adjacent particles and between particles and walls. The data were correlated by dimensional analyses and were represented by

$$\frac{Nu}{Pr^{0.5}} \left(\frac{\rho_b}{\rho_g}\right)^{0.18} \left(\frac{\rho_b C_p}{\rho_g C_s}\right)^{0.36} = 0.58 (B Re)^{0.45} \quad (12)$$

The correlation is valid for the range of the modified Reynolds number $0.1 < B D_p G/\mu < 5.0$. B is a generalized shape factor.

Toomey and Johnstone (29) presented the data for the transfer of heat from a central electric heater to a vertical fluidized bed. The apparatus was provided with glass windows for observing the particle movement in the bed and the bed was constructed in sections to evaluate

the bed height effect. The data were correlated by the equation:

$$\frac{h D_p}{K_G} = 3.75 \left(\frac{D_p U_{mf} \rho}{\mu} \log \frac{U}{U_{mf}} \right)^{0.47} \quad (13)$$

where U_{mf} = minimum superficial velocity necessary for fluidization.

Wen and Leva (30) used the data of Dow and Jakob (26) of Van Heerden et al (27), of Leva et al (21) and of Toomey and Johnstone (29) to obtain a generalized correlation for h_W :

$$\frac{h_W D_p}{K} = 0.16 \left(\frac{C_S \rho_S D_p^{1.5} g_c^{0.5}}{K} \right) \left(\frac{D_p G}{\mu} \cdot \frac{\eta}{R} \right)^{0.36} \quad (14)$$

where η is the fluidization efficiency and R is the bed expansion ratio.

Wender and Cooper (31) published some correlations of heat transfer data to surfaces. Nine sources of data from the literature were considered. Separate correlations were provided for heat transfer to external surfaces, that is, the bed walls, and to internal surfaces, represented by immersed tubes or similar devices. These authors summarized and discussed questions of mechanism.

Spouted bed:

Klassen and Gishler (32) obtained heat transfer data for heat flowing from a steam jacket to a packed bed, fluidized bed and spouted bed. In the case of a spouted bed they found a sharp increase in the rate of heat transfer at the onset of spouting. The maximum heat transfer coefficient was 25-75% lower for a spouted bed than for a fluidized bed under similar flow conditions. Rice, wheat and Ottawa sands were used as bed materials.

Ghosh and Osberg (33) investigated the heat transfer from a 9-in. steel column wall to water spouted sand beds. The heat transfer rates to water flowing through a spouted bed was lower than when the column was empty probably as a result of the suppression of convection currents. At the same water flow rate, the spouted bed gave a lower rate than a fixed bed because a large fraction of the water by-passed the wall region and flowed up the spout.

No correlation is available for calculating the heat transfer coefficient in a spouted bed.

EXPERIMENTAL

General consideration of apparatus:

Spouted bed:

Considerable thought was devoted to the design of the experimental apparatus. Reliable data can be obtained only if the design of the apparatus affords accurate measurements of data. In order to design the final equipment, a preliminary plexiglass column was built to study the flow pattern of the air and solid particles. The plexiglass column was 6-in. inside diameter and 48 in. long. Experiments with wheat-I in this column revealed that the particle velocity varied all along the bed height and that the distribution of air velocity in the column was highly non-uniform. Since the heat transfer and momentum transfer are closely related in a bed, it is possible that the heat transfer coefficient may be a function of bed height. If this assumption is right, the heat transfer coefficients of any arbitrary section would not reveal the true picture for the whole bed. It is desirable to obtain the point heat transfer coefficients or at least an average coefficient which is taken over as small a height as practicable. Such a coefficient would give a better insight into the mechanism of heat transfer and it would also enable a study of vertical variation within the bed. To obtain these results, the final column was constructed as described below.

Column:

The general layout of the apparatus is shown in Fig. 1 and

Fig.1. EQUIPMENT LAYOUT

Fig. 2. 6" Section column - (I) Shows the cooling water arrangements - (II) Shows the thermocouple arrangements.

the details of different sections with water and thermocouple connections are shown in Fig. 2.

Two different size units were used, the inner tube diameters being 6.0-in. and 3.0-in., respectively. The total length was 38 in. in both cases and both were fitted with a 60° cone at the base. The large column was surrounded by a jacket of 7.5 inch inside diameter and the small column was surrounded by a jacket of 4.0 in. inside diameter. The annulus in both cases was divided into five water-tight sections, the length of different sections for the large column being 3.6, 3.6, 5.0, 6.8 and 19 inches, and for the small column being 6.0, 6.0, 7.0, 7.0 and 12.0 inches from the bottom of the column. In both cases, the cone was surrounded by a jacket, the clearance between the jacket and the cone being 1/2 inch. Starting from the air entrance, each section including the cone was numbered as 1, 2, 3, 4, 5 and 6, respectively.

Two water connections were placed on each section, an inlet near the bottom and an outlet near the top of each section. The outlet was tapped for a 3/8 in. nipple and a 3/8 in. tee (T) was connected to the nipple. For inlet fittings, 1/8 in. holes were drilled at the annulus wall perpendicular to the radius and these holes were tapped for 3/8 in. nipple. These arrangements facilitated the water flow around the column in one direction avoiding local cooling and maintained a constant wall temperature at any level. All the inlets were connected to a stainless steel surge tank.

Both columns were fitted on a 2-1/2 in. inside diameter x 3 ft. long steel pipe. To straighten the air flow, 18 copper tubes (1/4" I.D.

x 18 in. long) were placed inside the 2-1/2 inch steel pipe.

The orifice plate, 1/16 in. thick was placed in between the cone and the steel pipe. Since this plate was sitting in a groove on the flange of the 2-1/2 in. pipe, it could be inserted or removed easily by lowering the support pipe.

About one inch above the orifice plate and at the bottom of each section, 1/16 in. stainless steel tubings were soldered at the inner wall of the column to measure the static pressure at the different bed levels.

Thermocouples:

Before the sections were assembled it was necessary to place the thermocouples in positions. Two thermocouples were used to measure the wall temperature of each section. They were placed at a distance of 1/2 in. from either end. For each thermocouple a groove 1/4 in. wide, 3/16 in. deep and 1 in. long was cut on the outside of the inner wall. The junction of the iron constantan thermocouple (24 in. gauge) was silver-soldered to the metal at the end of the groove and the thermocouple leads to the top of the section were encased in a 1/16 in. ceramic tubing. The ceramic tubing was covered by soft solder and the resulting surface was ground smooth and levelled with the rest of the surface. The leads now passed through a 3/8 in. nipple, one end of which was silver-soldered to the inner wall and the other end passed through a hole made on the outer wall of the jacket.

It was desirable to obtain both radial and axial temperature profiles while interfering with the bed motion as little as possible. Therefore a single probe was built which could measure the radial and axial temperature gradient at different levels. Preliminary investigations in the plexiglass column indicated that even 1/16 in. thin rod interfered greatly with spouting when placed at the spout region from the top of the column, also the rod was oscillating all the time due to particle movement. This interference was minimized when the rod was introduced into the bed from the side. Accordingly, 1/4 in. holes were drilled 1 in. apart all along the column before assembly. The holes at the inner wall were tapped for 3/8 in. nipples. The nipples were soldered at the outer wall.

An iron-constantan thermocouple 12 in. long was bought from Honeywell. The outside diameter of the containing tube was 1/16 inch, and it was highly polished and gold-plated to minimize the heat transfer due to radiation. The thermocouple was mounted on a rack placed on a 6" x 8" x 1/16" plate. The rack could be pushed forward or backward by a small motor. The whole assembly was fixed on a graduated vertical 1 in. aluminum rod. The plate with the thermocouple could be moved upward or downward along the vertical rod and the thermocouple could be moved forward or backward on the plate either manually or mechanically. The mechanical operation had to be abandoned since it was found out later on that, due to the fluctuation of temperature, it took about 1-5 minutes to measure the temperature at certain points.

All thermocouple leads were brought to a central panel through a 1 in. conduit. Both the leads were connected to standard copper thermocouple wire in a cold junction at 0°C. The cold junctions were in glass wells made of 6 mm. glass tubing by closing one end and filling them with anthracene. Twelve tubes were held in a two-litre vacuum bottle such that about an 8 in. section was submerged in finely cracked ice.

The thermocouple leads were connected to a Honeywell Model No. 153X18-V-11-111-157 continuous recorder through a sixteen point selector switch.

Water system:

Since the supply pressure was fluctuating all the time, an overhead tank 2 ft. I.D. x 3 ft. high was built and placed about 5 ft. above the column. All the inlet lines were connected through valves to a 1 in. pipe leading from the overhead tank. The water rate could be fixed at any section at any rate without much difficulty, since the overhead tank maintained the supply pressure constant. The inlet and outlet water temperatures were measured by mercury-in-glass thermometers.

Air system:

Air was supplied at 125 lbs/sq.in. by two air compressors. Since this pressure was fluctuating all the time, a pressure regulator was placed in the line to supply the air at 40 lbs/sq.in. The air passed through two filters, a dryer, a rotameter and a heater before entering the column. The filters removed oil, dust and water and the dryer removed

last traces of moisture. The dryer was a 4 in. inside diameter x 5 ft. long column filled with silica gel. There were two inspection spots on the wall to observe the colour of the silica gel. A Chromalox air heater, Model No. GCH-36, was used to heat the air. There were two systems to control the air temperature. The rough one controlled the air temperature to within $\pm 5^{\circ}\text{F}$ and the fine one to within $\pm 0.5^{\circ}\text{F}$.

A Brook's Rotameter Tube size 12-9M-25-2, Ser.-11532-1 used for measuring the air flow had a maximum capacity of 50 CFM.

Regeneration of silica gel:

The silica gel lost its activity at the end of about ten hours' run. Arrangements were made to regenerate it inside the dryer. During regeneration, the valves 2, 3, 5 and 6 (Fig. 1) were closed and the air entered the heater through valves 7 and 4, then went to the dryer through valve 8 and out to atmosphere through valve 9. Hot air at about 300°F passed through the dryer and it took 5-6 hours for regeneration.

OPERATIONAL PROCEDURE

For each run the desired amount of particles was poured into the column from the top. For all the experiments the supply pressure of air was maintained at 40 psig by the pressure regulating valve. The air entered the column through the two filters, the dryer, the rotameter and the heater. The valves 1, 2, 3, 4, 5, and 1, 2, 3, 4 and 6 were opened for the operation of large and small columns, respectively. The heater was adjusted to heat the air to the desired temperature. The water flow to different sections was adjusted to give a reasonable temperature increase of the water as well as a reasonable temperature drop at the wall. At least six hours were required to reach steady state conditions. When all the temperatures had become constant, the data for a given run were taken. Flow measurements for air and water lines and temperature of all the thermocouples were recorded for each run. The experimental section or sections were kept at isothermal condition by regulating the water supply at the two end sections. This arrangement minimized the heat loss or gain from the experimental section or sections to or from the end sections.

The particle breakup was a serious problem in this work. The materials included in this work were chosen after numerous solids had been tried. Many materials, for example, corn, sunflower, rape seed, match sticks and wood chips, had to be ruled out due to their excessively high attrition rate and granulated cork for static electricity.

It was decided to examine how closely air temperatures were measured by the bare couples used in the tube. Bed temperatures of wheat-I, polyethylene 2 and Timothy seeds were explored at different bed levels by two identical iron-constantan thermocouples, one of which was bare while the other was covered by a fine screen in order to prevent solids from contacting the junctions. The two couples were tied together inside a copper tube and bed temperatures were recorded at different bed levels by introducing the thermocouple in the bed from the side. The protected thermocouple measured only air temperatures whereas the bare thermocouple indicated some temperature between air and solids. The temperature difference recorded by the two couples at the annulus was found to be negligible up to the top of the cone. It was not possible to measure the temperature of the bed at the cone region with the two thermocouples since the side opening was too small. The difference in reading between the two couples was appreciable in the spout just over the cone; but this difference decreased with the increase of bed level, and near the top of the bed both couples gave nearly the same reading.

Fluidized beds:

To compare the heat transfer data of spouted and of fluidized beds under similar conditions, fluidized bed heat transfer data were obtained with wheat 1, 2 and 3 as bed materials in the 6-in. column used for spouting. The orifice plate from the bottom of the cone was removed and a porous stainless steel filter sheet was placed in between the column and the cone as a support for the bed materials.

- 24 -

The experimental procedure was the same as described earlier for the spouted bed. The bed materials, particularly wheat-1, fluidized very poorly because of severe slugging.

SOLID PARTICLES

Different sized particles of the same materials were numbered 1, 2, 3, etc. Wheat, rice, millet and Timothy seeds were bought from the local market and polyethylene and polystyrene were supplied by Dow Chemicals of Canada Ltd. Rice, millet, Timothy seeds and wheat of size 1 and 2 were regular in shape, but wheat 3 and 4 were obtained by crushing regular wheat and screening it. Polyethylene 1 and 2 were cylindrical and 3 was spherical and polystyrene 1, 2 and 3 were cylindrical in shape.

Physical properties

The physical properties of the bed materials were measured. These properties included bulk densities, absolute densities, particle size and shape, void fraction, thermal conductivity and specific heat. These properties of each of the materials are listed in Table I.

Bulk density, ρ_b

The bulk density was determined by weighing the quantity of material needed to fill a two-litre cylinder. The materials were poured into the cylinder through a funnel from a two-inch height in one minute's time.

Absolute density, ρ_s

The absolute density was determined by the method of liquid displacement in a pycnometer and by air displacement in a Beckman Model 930 Air Comparison Pycnometer.

TABLE 1. Physical Properties of Solid Materials

Particle diameter in.	Absolute density of particles lbs/cu.ft.	Bulk density of particles lbs/cu.ft.	Void fraction δ	Shape factor λ	Thermal conductivity of solid material Btu/(hr)(ft)(°F)	Specific heat of solid material Btu/(lb)(°F)	
Wheat-1	0.1494	82.000	51.600	0.4200	1.073	0.181	0.354
Wheat-2	0.1420	89.040	52.040	0.4156		0.181	0.354
Wheat-3 (-9, +12)	0.0718	89.619	52.041	0.4193		0.181	0.354
Wheat-4 (-12, +16)	0.0503	89.620	52.297	0.4165		0.181	0.354
Rice-1	0.1071	90.948	56.472	0.3790	1.041	0.194	0.356
Rice-2	0.0885	91.029	52.540	0.4229		0.194	0.356
Polyethylene-1	0.1350	57.576	36.966	0.3580	1.020	0.201	0.550
Polyethylene-2	0.1185	56.160	36.217	0.3552		0.201	0.550
Polyethylene-3	0.0524	64.896	42.430	0.3462		0.201	0.550
Polystyrene-1	0.1254	66.019	37.000	0.4396	1.141	0.068	0.280
Polystyrene-2	0.0616	66.019	35.256	0.4660	1.176	0.068	0.280
Polystyrene-3	0.1055	65.520	38.226	0.4166		0.068	0.280
Millet	0.0783	73.690	45.365	0.3840	1.07	0.133	0.345
Timothy	0.0343	70.910	39.000	0.4500		0.160	0.374
Sand (-16, +28)	0.0311	164.450	90.355	0.4599		0.190	0.191

Particle diameter, D_p

For any irregular particle we may substitute an equivalent particle: a cube, sphere or other geometrical figure having the same volume or surface. It is customary to reduce a particle to an equivalent sphere, using a single parameter, the distance between the extreme limits of a particle along a fixed direction. With knowledge of the number of particles used in each test and the amount of liquid displaced during the absolute density measurements, the volume of one particle was determined and this volume was equated to a hypothetical sphere having an equivalent diameter as follows:

$$D_p = \left(\frac{6 \times \text{volume of particle}}{n} \right)^{1/3} \quad (15)$$

The particle size of Ottawa sand and wheat 3 and 4 were determined with a Tyler Sieve by considering the arithmetic average of the two appropriate screen sizes.

Shape factor

The shape factor were calculated by using Isha's equation
(23)

$$\lambda = 0.205 \frac{s}{v_p^{2/3}} \quad (16)$$

To calculate the surface areas, the dimensions of about 50 particles were measured by a travelling microscope and a micrometer.

Porosity, δ

The porosities were calculated from a knowledge of the bulk density and absolute density by using the following equation

$$\delta = 1 - \frac{\rho_b}{\rho_s} \quad (17)$$

Thermal conductivity

Introduction:

The thermal conductivities and specific heats of most of the materials used for spouting are not available in the literature. The conductivity of a composite bed may depend upon (1) the conductivities of the solids and the gas, (2) the eddy thermal diffusivities, (3) the moisture content of the particles, (4) radiant heat transfer at high temperature and (5) porosity of the bed. The amount of gas phase and water content present play such an important role among the many factors which influence thermal conductivity that reported data in which porosity and moisture content have not been specified are almost meaningless for comparison with other results. If the data for the thermal conductivity of completely dense bodies are available, they could not be employed for most applications without some knowledge of the effects of other factors influencing the effective thermal conductivity. Similarly, it is extremely difficult to prepare completely dense bodies from most materials and particularly from seeds. In the case of fibrous materials, the problem is more complicated as the direction of the fibers influences the heat transfer.

In a packed bed the effective conductivity is more dependent upon the gas phase than upon the conductivity of the solid phase possibly because the solid forms the discontinuous phase and the gas forms the

continuous phase. In the case of a very fine granular system where interstitial dimensions are comparable to the mean free path of the gas molecules, the effective conductivity is found to be less than that of the gaseous phase (34, 35).

Experimental:

The apparatus used for measuring the thermal conductivity and specific heat is shown in Fig. 3. The material was contained in a galvanized cylinder 6 in. I.D. x 18 in. long, 20 gauge nichrome wire was used for heating purposes. Each end of the cylinder was closed by a 1-1/2 in. cork board. The seven iron constantan thermocouples were placed halfway down the cylinder at radii of 0.15, 0.65, 1.15, 1.65, 2.15, 2.65 and 3.025 in. Great care was taken to make sure that the thermocouples were located in proper position. In each experiment the particles were poured into the cylinder from a height of 3 in. and in two minutes' time. The thermocouples were connected to a Phillips 12 point recorder, type PR 4069 M/Q4 through ice point. The heating element was switched on when the particles were in equilibrium with the surrounding air. Each experiment lasted from 20 to 30 hours.

The heating current was supplied from the main supply through a variac, a Heathkit battery eliminator and an ammeter capable of reading to the nearest milliamperere or better.

The moisture content of the particles was determined by an oven method. Each sample was weighed, then dried in an oven at 105°C

Fig. 3. Diagram of apparatus used to measure the thermal conductivities of particles

to constant weight. The moisture content was calculated for each sample from its weight before and after drying and was expressed as a percentage of the dry air sample.

Theoretical consideration:

Heat transferred in a circular cylinder is given by the equation

$$\frac{\delta t}{\delta \tau} = \frac{K}{C_p \rho} \left(\frac{\delta^2 t}{\delta r^2} + \frac{1}{r} \frac{\delta t}{\delta r} + \frac{1}{r^2} \frac{\delta^2 t}{\delta \theta^2} + \frac{\delta^2 t}{\delta z^2} \right) \quad (18)$$

and reduces to

$$\frac{d^2 t}{dr^2} + \frac{1}{r} \frac{dt}{dr} = 0 \quad (19)$$

under steady state condition when the temperature is a function of radius only. The solution of equation 19 is

$$t = C_1 + C_2 \ln r \quad (20)$$

According to Carslaw (36) in a circular cylinder where the initial temperature is constant taken as zero, and heat is supplied at a constant rate along the axis of the cylinder, for steady state conditions the equation for heat flow is

$$t_r = \frac{I^2 R}{2\pi K} \ln a - \frac{I^2 R}{2\pi K} \ln r \quad (21)$$

where t_r is the temperature at radius r , I is the current, and R is the resistance per unit length of the heating element, a is the radius corresponding to boundary temperature conditions, and K is the thermal conductivity.

Comparing (20) and (21)

$$C_1 = + \frac{1^2 R}{2\pi K} \ln a \quad (22)$$

$$C_2 = - \frac{1^2 R}{2\pi K} \quad (23)$$

The values of C_2 may be obtained from the slope, C_1 and r from the intercepts of the equilibrium curve and K may be calculated either from (19) or (20).

The specific heat C_p may be calculated either calorimetrically or from the equation

$$C_p = K/\rho \gamma \quad (24)$$

Carslaw (36) gives the following solution for a cylinder when the initial temperature is a function of radius only and the surface is kept at zero temperature

$$t = \sum_n^{\infty} A_n J_0(a_n r) e^{-a_n^2 \tau \gamma} \quad (25)$$

where t is the temperature at time θ , $J_0(a_n r)$ is Bessel function of order zero of the first kind and a_n are the roots of $J_0(a_n) = 0$, and A_n is a constant determined from the initial temperature distribution.

From this, Babbitt (37) derived the equation for an experiment in which the surface of the cylinder was maintained at the initial or zero temperature and the final temperature was a function of the radius given by $t = C_1 + C_2 \ln r$, as

$$t = T - \sum_{n=1}^{\infty} A_n J_0(a_n r) e^{-a_n^2 \tau \gamma} \quad (26)$$

where T is the final temperature and

$$A_n = \frac{B \frac{a}{a_n} J_1(a_n a) + C \left[\frac{a}{a_n} J_1(a_n a) \ln a - \frac{1}{a_n^2} \right]}{\frac{a^2}{2} J_1(a_n a)^2} \quad (27)$$

γ may be calculated either from the experimental point chosen so that only one term of equation (26) is significant, or by evaluating the first few terms of the same equation as suggested by Babbitt.

Results:

The experimental results for thermal conductivity, diffusivity and specific heat are shown in Table 1 and temperature data are listed in Tables 43-50. A typical temperature profile is shown in Fig. 4. The thermal conductivity was calculated by using equation (23) and taking the value of C_1 from the slope of the curve obtained when the final temperatures are plotted against the logarithm of the radius. These equilibrium curves are drawn for each set and shown in Fig. 5. It is found from Fig. 5 that the temperature is not zero at the surface but at some point outside the cylinder. To use equation (23), the cylinder surface was not used as the true surface but an imaginary surface at a distance $r = a$ where $t = 0$.

To calculate the thermal diffusivity γ the value of A_n was calculated for the first ten terms in the series and shown in Table 51. As it was time-consuming to use many terms in the series for accurate

Fig. 4. Variation of temperature with time at different POSITIONS
MATERIAL - wheat

Fig. 5. Steady state temperature distribution

A) Wheat. B) Timothy

C) Polyethylene.

Fig. 5. Steady state temperature distribution

A) Flax seeds. B) Millet.

C) Sunflower. D) Rice.

results, experimental points were chosen instead so that only one term of the equation (26) is significant. The value of the thermal diffusivity at different radii, except for that of the first position, was calculated and the average value is listed in Table 1. The fluctuation of temperature was noticeable in position one due to the variation of the supply voltage.

The specific heat was calculated by using equation (24). The thermal conductivity of the particles was calculated by using the equation of Kunii and Smith (38).

Discussion:

The bulk thermal conductivity of wheat and the specific heat of wheat and polyethylene compare very satisfactorily with the literature value. The specific heat of the bulk material was taken as the specific heat of the solid material itself. Strictly speaking, this assumption is wrong, but the error introduced by this assumption is negligible. It may be pointed out that in case of wheat the air present at the void was only 0.093% on a weight basis. The amount of heat necessary to raise the temperature of this small amount of air is negligible.

The effective thermal conductivity of the moisture containing particles may be quite different if the mode of heating is changed even if the experiments are conducted at the same temperatures. The moisture in the particles migrates from points of high to points of low temperature and the latent heat exchanges upset the measurements. This migration of moisture and the exchange of latent heat may be different in various shaped apparatus due to different mode of heating. The thermal

conductivity of the particles has been calculated from the effective conductivity neglecting the heat transfer through the contact points and by radiation (17). It is quite justifiable to neglect the radiant heat transfer at low temperature, but it is not justifiable to neglect the heat transfer through the contact points unless the particles are perfect spheres. The model of Kuni and Smith (38) explains a good deal about the mechanism of heat transfer and its effect on the conductivity in a bed.

In a stagnant bed, the freedom of gas molecules may be different at different points due to the surface tension. Surrounding the bed particles there may be a layer of gas film and the thickness of this gas film may be different near the contact points. If this is true, the heat transfer coefficient of this film will be different from that of the gas. Again the nature of contact points is not a function of void fraction but a function of particle shapes. Spheres can only touch each other at points whereas cylinder cubes and other irregular shaped particles may touch each other on surfaces. In a general correlation for effective thermal conductivity all these factors should be considered. As it is beyond the scope of our present work to develop an equation for effective thermal conductivity, we consider it sufficient to use Kuni and Smith's (38) correlation to calculate the thermal conductivity of the particles from the effective thermal conductivity.

RESULTS

All the pertinent data covering each section are tabulated in the Appendix. The heat transfer coefficients between the wall and the bed are listed by sections and their average values are also shown.

The heat transfer coefficient was calculated from the observed data by means of the equation

$$h = \frac{Q}{A \Delta t_1} \quad (23)$$

The heat transfer rate Q was determined from the quantity of water flowing and the rise of water temperature. The temperature difference Δt was calculated from the surface temperature and the bed temperature at the annulus.

Limited data were collected from the cone region with wheat-I and polyethylene-2. The particle flow pattern as found by visual observation and temperature profile as shown in Fig. 6 for this region is complicated and much different from the rest of the bed. Since this region itself presents a complicated problem, no attempts were made to collect further data from it.

Effect of temperature:

To determine the effect of temperature on h_w , it was necessary to make runs at different bed temperatures holding all other variables constant. This procedure was followed when wheat-I was spouted at an air temperature of 180°F and 100°F. No significant effect of bed

Fig. 6. Typical temperature profile for a spouted bed in a 6" column, $\frac{3}{4}$ in. orifice and 13 in. bed height.

temperature on h was detected.

Effect of D_p on h :

For the application of the experimental data to design calculations it may be desirable to know the maximum benefit obtainable through the presence of the spouted solids. For this purpose, Fig. 7 has been presented showing the effect of particle diameter on h_w in the presence of spouted solids. The solid lines represent the data for wheat, polyethylene and polystyrene and may be represented by the equation

$$h = K D_p^{0.56} \quad (29)$$

where the constant K is a function of bed depth, heat capacity and density ratio of solids and air.

In Fig. 8 average h_w vs. G is plotted for various materials. Within the fixed and transition bed, h_w is found to increase with the mass velocity, the rate of increase being much more during the transition period. After spouting, h_w is found to be independent of G . In the transition bed h_w decreases with bed level whereas in the spouted bed h_w increases with bed level. (See Fig. 9).

It is found from Fig. 10 that average h_w decreases with increase of bed height whereas it is found from Fig. 11 that at a given bed height h_w of an individual section is higher at a higher bed level.

Fig. 7 Effect of particle diameter on heat transfer coefficient.
6 in. column, $\frac{1}{2}$ in. orifice and 18 in. bed height.

Fig. 8. Effect of mass velocity on heat transfer coefficient.
6 in. column, $\frac{3}{4}$ " orifice, 13 in. bed height.

Fig. 9. Effect of mass velocity on heat transfer coefficient.
6" column, $\frac{3}{4}$ " orifice, 13" bed height.

Fig.10 Effect of bed height on Nusselt number.

Fig. II Vertical heat transfer profile
6" column, $\frac{1}{2}$ " orifice, 18" bed height.

FLOW MECHANISM IN SPOUTED BEDS

To understand the heat transfer mechanism in a moving system, it is necessary to understand the flow pattern of the system. A discussion of spouting is presented to throw light on the flow pattern of air and solid particles. Observations in a semicircular column with plexiglass front indicated that the spouting of a bed might be broken up into three steps as the air rate through the bed increased:

- 1) Packed bed - the air passed through the bed without disturbing any particle.
- 2) Transition bed - A cavity was formed at the bottom of the bed and moved up to the top of the bed.
- 3) Spouted bed - The particles moved up the bed through the spout and returned through the annulus.

It is found from the pressure drop data that the boundary between the packed bed and the transition bed is uncertain, but it is quite distinct between the transition and the spouted bed.

The relationship between pressure drop and air flow rate is shown in Fig. 12 for wheat-I, spouting in the 6-in. column at 13-in. bed height. The pressure drops were recorded simultaneously at 1-in., 5-in., and 9-in. bed levels, respectively, from the orifice. With increasing flow rate the pressure drops increased; at a certain air rate a cavity or internal spout was formed lifting the particles upward from the air entrance and thus reducing the surrounding bed density. With still increasing air rate, some of the particles started whirling inside the

spout and reoriented themselves surrounding the internal spout. The particles seemed to orient themselves in such a manner as to present the greatest resistance to the fluid flow and to form a stable arch of particles; the particles are naturally not endowed with independent motion, therefore the orientation effect must result from consideration of particles dynamics. The thickness of the arch was different at different radii from the orifice centre. Away from the internal spout the particle population decreased gradually. The shape and nature of the particles' vorticity were difficult to reproduce.

The maximum pressure at B (in Fig. 12) seems to be a function of the shape and size of the spout, the stability of the surrounding arch, the particle vorticity and the bed height. At the point of maximum pressure drop, the internal spout experienced a considerable development (Fig. 13), whereas the bed was just on the verge of expanding. Since the bed had not expanded as yet, the reduction of the bed volume at the point of maximum pressure drop was equal to the volume of the internal spout. As the internal spout moved up the bed along with the surrounding arch, the bed expanded and the bed height over it decreased with subsequent decrease of pressure drop at the base, but the pressure drop at any section of the bed above the internal spout was still increasing. Up to the point of spout height the particles at the annulus moved downward whereas the whole bed above the spout was still stationary. At this stage, severe channeling at the wall above the spout was observed. It was interesting to note the particles moving downward at one height of the bed and moving upward or vibrating at another height. The bed

Fig. 12 Pressure drop-flow diagram
for a spouted bed (material-wheat 1)

x Pressure drop at bed level 1 in. from bottom.
 • " " " " " 5 in. " "
 o " " " " " 9 in. " "

6" column, $\frac{3}{4}$ " orifice.

porosity was found to be very nonuniform along the bed level. This complex phenomenon continued until the spout reached the top of the bed when the pressure drop remained approximately constant, the void fraction of the bed at the annulus was nearly uniform except at the two ends and the bed height decreased slightly, i.e. the void fraction of the bed was less during spouting than that during the transition period.

The particles followed a regular pattern during spouting as indicated in Fig. 14 and 15. They moved down at the annulus, up at the spout and there were cross flows along the bed level. Observations were made with wheat-I to determine the order of magnitude of the particle velocity at the wall. Colored particles were followed and timed for certain distance during their fall. In general, the particle velocity was found to increase with the bed level, and with the bed height, Fig. 16. No attempts were made to find the probable variable affecting particle velocity. The particles definitely did not descend as free-falling bodies in a gas stream, but they had a regular downward motion.

Temperature exploration throughout the spouted bed, as shown in Fig. 6, indicated a sharp temperature drop at the column wall at any bed level. However, this drop at the spout wall was a function of bed level. At lower levels, especially in the cone region, the temperature drop was very sharp at the spout wall and it flattened out gradually with bed level. In between the spout wall and about $1/4$ in. to $1/2$ in. from the column wall, the temperature of the bed was fairly constant. It may be concluded that there are two resistances to heat flow in parallel in a spouted bed - one at the spout wall, and the other at the column wall.

Fig. 13. Internal spout at point of maximum pressure drop

Fig. 14. Particles flow pattern in a spouted bed

Fig. 15 Heat transfer mechanism and air and particles flow.

An attempt was made to calculate the heat transfer coefficient at the spout wall by the following equation

$$h_s = \frac{Q_s}{A\Delta t}$$

where Q_s is the quantity of heat given up by the particles and the air to the annulus between two levels in the bed, A is the spout surface area between the two levels, Δt is the temperature difference between the spout and the annulus, and h_s is the heat transfer coefficient at the spout wall. To calculate the quantity of heat Q_s , it was necessary to know the amount of solids and air flow between the two levels. The quantity of air flow through the spout was taken from Mathur and Gishler's data (3). The volumetric flow of solids through the annulus was calculated from the annulus cross-sectional area and the particle velocity at the wall (see Fig. 16) assuming that the particle velocity at the wall and the downward movement of the bed at the annulus were the same. In a spouted bed, at any level, the particle flow through the annulus and the spout are the same. Since in a full column the spout was not in view, separate experiments were conducted in a 6-in. semicircular column with plexiglass front to find the spout diameter and thereby to calculate the spout and annulus cross-sectional area. It is clear that to understand the flow pattern of the fluid and solid in a spouted bed, one must know the dimension of the spout in the bed. A generalized correlation

$$D_s = (0.115 \log D_c - 0.031) G^{0.5} \quad (31)$$

was developed to estimate the spout diameter (4) and the details are described in the Appendix.

The estimated h_g values were too high to be real (of the order of 1000 to 1500 Btu/(hr)(sq.ft.)(°F). The probable sources of errors may be the following: (a) the measurement of bed temperature by the 2nd thermocouple may not be correct as the spout height decreased considerably with a thicker thermocouple and at the same time the spout was displaced from the column centre; (b) the assumption that the particle velocity at the wall and the annulus velocity are the same may not be correct. Since the amount of air present in the bed was small compared to that of the particle, a small error in the estimation of the quantity of particle flow may upset the whole picture. However, from these calculations, it was observed that the amount of heat transferred from the air in the spout to the annulus was not significant.

From the foregoing discussion it must be clear that the mechanism of heat transfer is quite complicated in a spouted bed during transition and spouting period. During spouting the particles follow a definite regular path as shown in Figs. 14, 15. The particle velocity decreases as they move downwards indicating that there is a steady cross flow of solids from the annulus into the spout along the bed height. The radial gradient of particle velocity in the annulus is not appreciable. In a fixed bed a mechanism of heat transfer is visualized whereby the resistance to heat flow between the container wall and the bed is due to an extremely thin air film which forms at the interior tube wall. The scouring action of the air reduces the thickness of this film and thereby increases the heat transfer coefficient.

Fig. 16. Effect of bed height on particles velocity at wall.

(Material = Wheat 1)

6" column, $\frac{3}{4}$ " orifice.

The presence of a thin film at the interior tube wall in a spouted bed is also assumed in this study and this film thickness is reduced by the scouring action of the air and the down flow of particles along the wall. Heat is transported from the spout to the annulus by air all along the bed level by solid particles as they descend down the annulus from the top. Temperature exploration indicates that heat exchange between particles and hot air takes place at the spout and steady state condition is established before they reach the top of the bed. From the heat capacity consideration it is found that the heat capacity of wheat is about a thousand times more than that of air while the mean particle velocity is at most only 5 times lower than the air velocity at the annulus. Therefore, the convective transport of heat by moving particles is the primary factor in carrying heat from the centre to the wall of the column. The magnitude of the eddy conductivity brought about by circulation of the particles is calculated by conducting an experiment as follows. For a bed depth of 12" in a 6" plexiglass column, some colored wheat was introduced on the top of the spouted bed, and the time interval between the addition of the tracer and the establishment of visual uniformity of the colored material through the entire bed was then measured with a stopwatch. It was found that in about 40 seconds the tracer material distributed itself uniformly in the bed. Now the eddy diffusion coefficient of the particles can be calculated from the relation (39,27).

$$D_{\text{eddy}} = \frac{L^2}{2T} = \frac{.562}{80} = .00704 \text{ ft}^2/\text{sec.} \quad (32)$$

where τ is the time in sec. and L is the bed height in ft. Therefore the corresponding eddy thermal conductivity of the particles can be estimated as

$$\begin{aligned} K_{\text{eddy}} &= \rho_b C_s D = 51 \times .354 \times 7.4 \times 10^{-3} \times 3600 \\ &= 482 \text{ BTU}/(\text{hr})(\text{ft})(^{\circ}\text{F}) \end{aligned} \quad (33)$$

This exceptionally high figure indicates the importance of the convective transport of heat by the moving particles.

It has been shown (40) that when a sphere is brought suddenly into an environment at a different temperature, the temperature gradient within the small particles are negligible throughout the process. Therefore, the heat transfer coefficient between the tube wall and the spouted bed should be independent of the thermal conductivities of the solids. According to Ruedenberg (41), for a single particle the heat transfer coefficient to the surrounding particles is $2K/D_p$. Now the thermal relaxation time τ necessary to reduce a temperature difference initially present between the particle and its surroundings to one tenth of its original value may be calculated from a heat balance on the particle equating the change in heat capacity with the convective heat loss:

$$\rho C_p V \frac{dt}{d} = -h A (t - t_f) \quad (34)$$

which could be ultimately written as

$$\frac{t}{t_0} = e^{-(hL/K)(\tau/L^2)} \quad (35)$$

where

$$\nu^g = t - t_f$$

$$\frac{hL}{K} = \text{Biot modulus}$$

$$\frac{\tau Y}{L^2} = \text{Fourier modulus}$$

Substituting $h = 2K/D_p$ and $\frac{\nu^g}{\nu_o} = 0.1$

$$\tau = \frac{2.303 \rho_s C_s D_p^2}{4K} \quad (36)$$

Substitution of the numerical value in the above equation for wheat-1 yields a value of 0.064 seconds for τ . Thus it is seen that thermal equilibrium is established very rapidly between adjacent particles.

In conclusion it may be stated that the high heat transfer rate between a spouted bed and the container wall is caused by the scouring action of the air and the particle movement at the wall as well as by the convective transport of heat by the moving particles.

CORRELATION OF DATA

Previous discussion throws light on the particle movement and mechanism of heat transfer in a spouted bed. Considering the complexity of the bed, it was decided to correlate the data with dimensional analysis using the probable variables which affect the heat transfer coefficient. The factors which may affect heat transfer are shown in Table 2 with dimensions. The mass velocity G was omitted since the heat transfer coefficient was found to be independent of mass velocity after spouting within the experimental range.

TABLE 2

Factors which may affect heat transfer in a spouted bed

<u>Factor</u>	<u>Symbol</u>	<u>Dimensions</u>
Effective particle diameter	D_p	L
Apparent particle density	ρ_b	ML^{-3}
Specific heat of particle	C_s	$H M^{-1} T^{-1}$
Density of air	ρ_b	ML^{-3}
Viscosity of air	μ	$M L^{-1} \theta^{-1}$
Thermal conductivity of air	K_g	$H L^{-1} \theta^{-1} T^{-1}$
Bed height	L	L
Average heat transfer coefficient	h_w	$H \theta^{-1} L^{-2} T^{-1}$

The shape of the particles, which may be involved, was neglected.

Acceleration due to gravity was included since this affects the movements of the solid particles.

The dimensional analysis resulted in the following equation of dimensionless groups.

$$\frac{hD_p}{K_g} = K \left(\frac{L}{D_p}\right)^a \left(\frac{D_p^3 \rho_g^2 g}{\mu^2}\right)^b \left(\frac{\rho_b c_s}{\rho_g c_g}\right)^c \left(\frac{\rho_b}{\rho_g}\right)^d \left(\frac{C_p \mu}{K}\right)^e \quad (37)$$

The Prandtl number was constant for all experimental runs as only air was used and it was absorbed in the constant coefficient. The influence of modified Reynolds number on modified Nusselt number is shown in Fig. 17 for different materials with bed depth and orifice diameter as parameters.

The exponent b in equation (37) is evaluated by plotting Nusselt number against bed height with D_p as a parameter in Fig. 10. An average of all substances gives

$$\frac{hD_p}{K_g} = \text{constant} \left(\frac{L}{D_p}\right)^{-0.17} \quad (38)$$

In Fig. 18

$$\frac{hD_p}{K_g} \times \left(\frac{L}{D_p}\right)^{0.17} \text{ vs. } \left(\frac{D_p^3 \rho_g^2 g}{\mu^2}\right) \quad (39)$$

are plotted, all other variables remaining constant, and the value of exponent b found to be 0.52. The curves for different materials may be represented by the following equations.

Polyethylene:

$$\frac{hD_p}{K_g} = 8.7 \left(\frac{D_p}{L}\right)^{0.17} \left(\frac{D_p^3 \rho_g^2 g}{\mu^2}\right)^{0.52} \quad (40)$$

Rice:

$$\frac{hD_p}{K_g} = 8.2 \left(\frac{D_p}{L}\right)^{0.17} \left(\frac{D_p^3 \rho_g^2 g}{\mu^2}\right)^{0.52} \quad (41)$$

Fig.17 Effect of modified Reynolds number on modified Nusselt's number.
(6" column, $\frac{3}{4}$ " orifice, 13" bed height)

Fig. 18. Determination of exponent b in the equation (37)
 6" column, $\frac{1}{2}$ " orifice, 18" bed height.

Polystyrene:

$$\frac{h D_p}{K_g} = 6.3 \left(\frac{D_p}{L} \right)^{0.17} \left(\frac{D_p^3 \rho_g^2 g}{\mu^2} \right)^{0.52} \quad (42)$$

Wheat:

$$\frac{h D_p}{K_g} = 7.7 \left(\frac{D_p}{L} \right)^{0.17} \left(\frac{D_p^3 \rho_g^2 g}{\mu^2} \right)^{0.52} \quad (43)$$

The data for all the materials investigated may be brought together by considering the influence of the heat capacity ratio $\frac{\rho_b c_b}{\rho_g c_g}$ and density ratio $\frac{\rho_b}{\rho_g}$. The intercepts I_i of different lines in Fig. 18 are functions of heat capacity ratio and density ratio $\frac{\rho_b}{\rho_g}$. The exponents b and c are evaluated from the following four equations by least square methods and found to be 0.45 and -0.08, respectively.

$$I_1 = 8.7 = \text{constant} (1210.20)^b (513.80)^c \quad (44)$$

$$I_2 = 6.3 = \text{constant} (586.52)^b (491.00)^c \quad (45)$$

$$I_3 = 7.7 = \text{constant} (1025.82)^b (695.2)^c \quad (46)$$

$$I_4 = 8.2 = \text{constant} (1078.95)^b (726.75)^c \quad (47)$$

The final correlation of all the experimental data is shown in Fig. 19 and the straight line shown may be represented by the equation

$$\frac{h D_p}{K_g} = 0.54 \left(\frac{D_p}{L} \right)^{0.17} \left(\frac{D_p^3 \rho_g^2 g}{\mu^2} \right)^{0.52} \left(\frac{\rho_b c_b}{\rho_g c_g} \right)^{0.45} \left(\frac{\rho_g}{\rho_b} \right)^{0.08} \quad (48)$$

Fig. 19. Final heat transfer correlation for spouted bed.

TRANSITION SECTION

It has been explained earlier that the transition bed comprises the period from the formation of the internal spout to its venting to the bed surface.

Heat transfer data of transition period were collected for polyethylene 1, 2 and 3, polystyrene 1 and 2, wheat-1, rice-1 and millet with bed height, column diameter and orifice diameter as parameters. The experimental data and the literature information (42) indicate that duration of transition period depends on those variables such as D_p , D_c , L , ρ_b , ρ_g and g which affect the minimum spouting velocity. The factors which may affect heat transfer are shown in Table 3 with dimensions.

TABLE 3

Factors which may affect heat transfer in the transition period

<u>Factors</u>	<u>Symbol</u>	<u>Dimensions</u>
Effective particle diameter	D_p	L
Apparent particle density	ρ_b	ML^{-3}
Specific heat of particle	C_p	$HL^{-1} T^{-1}$
Density of air	ρ_g	ML^{-3}
Viscosity of air	μ	$ML^{-1} s^{-1}$
Thermal conductivity of air	K_g	$HL^{-1} s^{-1} T^{-1}$
Mass velocity of air	G	$M s^{-1} L^{-2}$
Bed height	L	L
Column diameter	D_c	L
Orifice diameter	D_i	L
Average heat transfer coefficient	h	$HL^{-1} L^{-2} T^{-1}$

Since the effect of bed height, column diameter and orifice diameter on heat transfer was not investigated, the following equation of dimensionless groups resulted with dimensional analysis without considering those variables.

$$\frac{h D_p}{K_g} = K \left(\frac{D_p G}{\mu} \right)^a \left(\frac{D_p^3 \rho_g^2 g}{\mu} \right)^b \left(\frac{\rho_b C_g}{\rho_g C_g} \right)^c \left(\frac{C_p \mu}{K} \right)^d \left(\frac{\rho_b}{\rho_g} \right)^e \quad (49)$$

The Prandtl number was absorbed in the constant coefficient since only air was used.

The values of exponent a, b are evaluated graphically. From Fig. 17 it is found that Nusselt number can be expressed as a function of Reynolds' number for all the materials investigated by the following equation:

$$Nu = \text{Constant } Re_m^{2.80} \quad (50)$$

In Fig. 20 plots of $\frac{Nu}{Re_m^{2.80}}$ vs. $\left(\frac{D_p^3 \rho_g^2 g}{\mu^2} \right)$ are shown for polyethylene 1, 2 and 3, polystyrene 1, 2 and wheat 1, and in Fig. 21, $Nu \left(\frac{D_p^3 \rho_g^2 g}{\mu^2} \right)$ vs. Re_m are shown for the same materials. These curves in Fig. 21 may be represented by the following equations:

$$\frac{h D_p}{K_g} = 0.00019 \left(\frac{D_p G}{\mu} \right)^{2.80} \times \left(\frac{\mu^2}{D_p^3 \rho_g^2 g} \right)^{-1.10} \quad (51)$$

Polystyrene

$$\frac{h D_p}{K_g} = 0.00014 \left(\frac{D_p G}{\mu} \right)^{2.80} \left(\frac{\mu^2}{D_p^3 \rho_g^2 g} \right)^{-1.10} \quad (52)$$

Fig. 20. Determination of exponent b in the equation (49)
 6" column, $\frac{3}{4}$ " orifice, 13" bed height.

Wheat

$$\frac{h D_p}{K_g} = 0.000165 \left(\frac{D_p G}{\mu} \right)^{2.80} \left(\frac{\mu^2}{D_p^3 \rho_g^2 g} \right)^{1.10} \quad (53)$$

The intercepts I of the three lines in Fig. 21 are functions of heat capacity ratio $\frac{\rho_b C_B}{\rho_g C_g}$ and density ratio $\frac{\rho_b}{\rho_g}$. The exponents d and e are found to be 0.58 and -0.25 respectively from the following simultaneous equations. It is not possible to determine them graphically.

$$I_1 = 1.90 \times 10^{-4} = \text{constant} (1210.2)^a (513.8)^b \quad (54)$$

$$I_2 = 1.40 \times 10^{-4} = \text{constant} (586.2)^a (491.0)^b \quad (55)$$

$$I_3 = 1.65 \times 10^{-4} = \text{constant} (1014.8)^a (589.0)^b \quad (56)$$

The final correlation is shown in Fig. 22 and is represented by the equation:

$$\frac{h D_p}{K_g} = 3.5 \times 10^{-5} \left(\frac{D_p G}{\mu} \right)^{2.8} \left(\frac{\mu^2}{D_p^3 \rho_g^2 g} \right)^{1.1} \left(\frac{\rho_b C_B}{\rho_g C_g} \right)^{0.43} \left(\frac{\rho_b}{\rho_g} \right)^{0.22} \quad (57)$$

Fig. 22. Final heat transfer correlation for transition bed.

DISCUSSION OF EXPERIMENTAL RESULTS

Temperature measurement and calculation of h_w :

It is evident from equation 28 that the magnitude of h_w is dependent on the numerical value of the temperature difference chosen. Figures 6 and 23 show typical longitudinal and radial temperature profiles of the bed. It is difficult to obtain the average temperature of the bed at any cross section from an integration of the corresponding temperature distribution curve since neither the composition of the solid air mixture nor the flow rate of the mixture can be easily measured. Also, a continuous record of temperature at a certain point in the bed indicated rapid fluctuations.

Ghosh and Osberg (33) noted this difficulty in the wet spouted bed and obtained the overall temperature difference as follows. The inlet water temperature and Δt at the inlet, i.e. at the bottom of the section under consideration was obtained by direct measurement. Since the bed remained confined within a section of the column, the total heat transferred through the wall was ultimately carried out of the section by the water flowing through the bed. The "mixing cup temperature" of the water leaving the section, and hence Δt at the top of the section under consideration, was obtained by calculation from the inlet water temperature, the water flow rate, and the rate of heat transferred in the section. An arithmetic average of the Δt 's at the bottom and the top of the section was used in Equation 28 for calculating the average overall heat transfer coefficient.

In this investigation, it was observed that the heat transfer coefficients in spouted beds are definitely not independent of bed height. For this reason it is not permissible to evaluate an average temperature difference simply by using terminal temperature differences. Therefore, the column was divided into different sections to evaluate bed height effects. Whereas a column constructed of one continuous section will permit only the relationship between coefficients and the bed height as a whole to be evaluated, sectional construction has the advantage that near-differential conditions are approached and local coefficients may thus be observed.

As demonstrated in Fig. 6, it is found that flatness is a characteristic of annulus temperature except near the wall, and the annulus temperature is nearly the same all through the bed. Therefore, it was decided to take Δt as the temperature difference between the annulus and wall temperatures. At the upper section of the bed, the spout temperature and the annulus temperature are nearly the same. No doubt this procedure gives the most conservative estimate of heat transfer coefficient, about 5% less than what one would obtain by considering the difference between the average bed temperature and the wall temperature. When using this for design purposes, one would always be on the safe side.

Figures 6 and 23 show the typical longitudinal and radial temperature profiles made inside the bed. Now the question arises whether a thermocouple immersed in a spouted bed will measure the

temperature of the solid or of the fluid, or perhaps some temperature average of both. The same problem has been discussed (12,43) in connection with fluidized beds. Since the two identical thermocouples, except inasmuch as one was shielded by a suitable wire screen to keep off the bed materials and the other couple was bare, give no significant difference in temperature at the annulus above the cone region; it follows that bare couples may be readily employed for thermal exploration of spouted beds for the purpose of obtaining heat transfer coefficients. As the entering air was hot the temperature difference between the spout and the annulus was very pronounced at the cone region, and this difference decreased with increase in bed level. Heat transfer took place between the air and the particles all along the bed level inside the spout and also from the air and the particles to the surrounding spout wall through a quasi film. It was not possible to calculate the heat transfer coefficient of this quasi film but it is reasonable to assume that the thickness of this film was a function of bed level since air and particle velocity varied along the bed level. The spout boundary may be considered as a porous wall through which hot air was escaping and particles were reentering.

A typical radial temperature profile pertaining to a wheat spouted bed is shown in Fig. 24 and compared with that of a fluidized bed. Marked similarity is observed between the two except that in the case of a spouted bed a temperature drop is observed at the spout boundary. In both cases a very steep temperature drop adjacent to the heat transfer surface is followed by a very flat course leading to the

Fig. 23. Typical vertical temperature profile in spouted bed.

$\frac{1}{2}$ " orifice, 18" bed height. (Material = polyethylene 2).

other boundary of the bed in the case of a fluidized bed and to the spout boundary in the case of a spouted bed. Three typical vertical temperature profiles pertaining to a polyethylene spouted bed are shown in Fig. 23. Curve II shows the temperature profile along the centre line of the bed, curve II at a distance of 1 inch from the centre and curve III at a distance of 2 inches from the centre line. Curve I shows close similarity to that of a fluidized bed. In both cases the unusually rapid temperature change is observed at the bottom of the bed and ultimately the temperature curves flatten out with bed level. This change of temperature is much sharper in the case of a fluidized bed indicating that in a fluidized bed thermal equilibrium between the gas and the solid particles is established at an earlier stage than in a spouted bed. The temperature profiles outside the spout (curve II and III in Fig. 23) are quite different and indicate that thermal equilibrium exists all along the bed height.

Hot particles enter the annulus at the top of the bed from the spout. On their way downward, the particles adjacent to the wall give heat to the transferring surface, transfer heat from one point to another radially by cross-flow and also meet the hot air coming straight up from below and also sideways from the spout.

Despite these obvious film effects at the column wall and spout wall, the extent of the lateral as well as vertical solids mixing in the vessel must be appreciated. That these factors are significant is indicated by the flatness of the temperature profiles at the annulus.

Distance from centre line of 6 inches column.

Fig. 24. Typical radial temperature profile in fluidized bed and a spouted bed.
(Material : Wheat 1)

Heat transfer to column wall

Profiles of heat transfer coefficients versus mass velocity are shown in Figures 8 and 9. In Fig. 9 heat transfer coefficients of an individual section for the transition bed and the spouted bed are shown and in Fig. 8 the average heat transfer coefficients of two sections are shown. In both the figures it is found that h_w increases with the mass velocity. In each curve there are three distinct traits - the flat portion representing h_w after spouting, the sharp steep portion representing h_w for transition bed, and the less steep portion representing h_w for the fixed bed. For a particular particle the heat transfer coefficients in a fixed bed in both the sections are the same. As soon as the internal spout starts moving upward, the bed materials up to the spout top are disturbed - they move downward very slowly through the annulus and upward through the spout. The heat transfer coefficient of the bed up to the spout head increases very sharply, whereas the corresponding rise of h_w above the spout head is relatively low, since the bed materials at this region are still undisturbed. At that stage, h_w of any section above the internal spout height is lower than that of those sections below the spout level. The rise of h_w increases with the increase of mass velocity and the subsequent advancement of the internal spout.

It has been stated earlier that when the internal spout made sufficient progress in the bed, severe channelling was observed near the column wall and the particle turbulence was quite noticeable. The heat transfer coefficient of the second section was greater than that of the

third section, since by visual observation it was noticed that the particles at the wall of the third section experienced two types of movements: vibrational movement due to channeling and a downward movement, whereas the particles at the lower level encounter only the downward movement. After spouting the heat transfer coefficient of the bed at any higher level was higher than that of lower level and it was found to be independent of mass velocity at any bed level within the experimental range.

In Fig. 25 the heat transfer coefficient of the spouted and fluidized beds is plotted against the corresponding mass velocity. Since we collected data only for fluidizing conditions, the data of Baerg and coworkers (44) are included in Fig. 25. On examining curve 3 in Fig. 25, it is found that along ab, fixed bed conditions prevail. Somewhere near b, the internal spout was formed. bc represents the heat transfer for the transition zone, i.e. the period of advancement of the internal spout from the orifice to the top of the bed; cd represents the heat transfer of the bed after spouting. From curve 1, it is found that ab is a fixed bed. At b', initial fluidization starts. As fluid velocity increases along branch c', the bed expands and, although for this section a continued increase in heat transfer is still evident, the rate of increase becomes progressively smaller until at d' maximum heat transfer coefficient is observed. Beyond point d' the heat transfer coefficient decreases. In curve 2, point d" indicates the maximum heat transfer coefficient for the experimental data. Comparing curve 1 and 2, it is found that in a fluidized bed the slope of the curve for the

Fig. 25. Effect of mass velocity on heat transfer coefficient.

smaller particles is much steeper than that of the large particles. This is quite understandable since the bed density of smaller particle is more sensitive to the variation of mass velocity.

The point of initial fluidization is quite distinct. When this point is reached, turbulence is created all through the bed. A spouted bed has a transition period between spouting and fixed bed. The heat transfer rate during the transition period as represented by the line b'c' in curve 3 is more than that of the fixed bed, but less than that of the fluidized bed. The flat portion of the curve bc is quite striking. After spouting, increased mass velocity did not show any noticeable variation in h_w within the experimental range. This finding is in contrast to what is found in a fluidized bed, where the heat transfer coefficient h_w first increases and then decreases with the increase of mass velocity. The reason is that in a fluidized bed an increase in average bed porosity is ordinarily caused by an increase in fluid rate.

Fig. 26 shows the effect of particle diameter on the spouted bed heat transfer coefficient and the maximum fluidized bed heat transfer coefficient. The solid lines represent the data for both the spouted bed and the fluidized bed and may be represented by the equation

$$h \text{ (spouted bed)} = K_1 (D_p)^{0.56} \quad (58)$$

$$h_{\max.} \text{ (fluidized bed)} = K_2 (D_p)^{-0.30} \quad (59)$$

where K_1 and K_2 are constant, and D_p is the particle diameter in inches.

Fig. 26 Effect of particle diameter on h_w in spouted beds and fluidized beds.
6" column.

The two curves in Fig. 26 show clearly that the smaller the particles, the lower the heat transfer coefficient for the spouted bed. In the case of the spouted bed, the spout diameter, bed height and particle velocity in the bed increase with increased mass velocity. It has been shown that (3) any extra air more than the minimum requirement for spouting passes through the spout. This indicates that in a spouted bed, increased mass velocity does not change the bed density which generally causes reduction of heat transfer in a fluidized bed.

On comparing the data of a spouted bed and a fluidized bed, it is found that for smaller particles the coefficient for a spouted bed is much lower than the corresponding fluidized bed (about 33%) and for larger particles, they are nearly equal (about 90%). The corresponding air requirement for spouting is only 35-55% respectively. Fluidization of large particles, usually larger than 1/8 in. diameter, is very poor. In the present experiment, wheat-I fluidized very poorly. Actually, the whole bed was bumping like a piston for a bed height of 8 in. and channeling was observed for a bed height of 5 in. In fact, the entire mechanism in spouting bears a very close resemblance to channeling as discussed by Leva (45). A comparison between channeling and spouting pressure drop curves (46) shows distinct similarities between the two systems. No wonder the heat transfer coefficient would be nearly the same in case of fluidization under channeling and spouting. During smooth fluidization of small particles turbulence is much greater compared with the smooth orderly laminar-like motion of the particles in the spouted bed system and the greater the difference in the heat transfer

transfer rates between the spouted and the fluidized state. This also shows that the effect of particle diameter on heat transfer coefficient in a spouted bed is the reverse of the trend for a fluidized bed. In the literature (24,29) it is found that the value of the exponent of D_p for a fluidized bed is about -0.78 for particle diameters varying from 0.001 to 0.04 in. Since the heat transfer coefficient depends on the fluidization quality, it is unlikely that the same correlation will hold for the bigger particles as they tend to slug or channel when subjected to fluidization.

The relationship between the modified Nusselt number and the modified Reynold's number is shown in Fig. 17 for a fixed bed, transition bed and spouted bed. One cannot find a single correlation to cover the whole range since the mode of flow pattern and heat transfer is different for different cases.

Effect of bed height:

The effect of bed height was investigated for all the materials and a plot of Nusselt number against the bed height is shown in Fig. 10 with particle diameter as the parameter. The experimental curve is represented by the equation

$$\frac{h D_p}{K_g} = \text{constant } L^{-0.17} \quad (60)$$

It is found that the smaller the particles, the steeper is the slope. To clarify this point from some qualitative observation further experiments were conducted in a Plexiglas 6-in. Full Column and 4-in. semicir-

cular column with Ottawa sand, Timothy seeds and wheat-1. It was found that the particle velocity at the wall decreased with the decrease of bed height - the rate of decrease was more pronounced for Timothy seeds and Ottawa sand and at a bed height of 9 inches there was hardly any movement of Ottawa sand at the wall. A cavity was found surrounding the spout and the sand particles entered the spout by sliding. The angle of sliding was much smaller than the cone angle. As a result, a considerable amount of materials surrounding the spout remained stationary and this caused the reduction of heat transfer. The larger particles entered the spout at the bottom of the column by following the geometry of the cone angle.

The effect of bed height on the fluidized bed heat transfer coefficient was not investigated. It is found to be controversial in the literature.

According to Dow and Jakob (26), coefficients varied as the 0.65th power of the bed height. Van Heerden and coworkers (27) did not notice any such influence, although their experiments were carried out under comparable conditions. They concluded that it was not the bed height which affected the coefficients, but the height of the heat transfer area instead. Toomey and Johnson (29) constructed the apparatus in such a way that heat transfer coefficients could be evaluated along the tube walls. They found that the variation of the heat transfer coefficient along the column wall occurs in two ranges. In type 1, the coefficient decreased slowly from a maximum at the bottom whereas in type 2, the coefficient increased to a maximum about half-way up the bed.

It is quite likely that the bed height will affect the heat transfer coefficient since Kramer's data (47) indicated that the uniformity in the bed was much better at the base than higher up and quality of fluidisation depended on (in addition to other factors) bed height.

The effect of bed height on transition period was not investigated. It is quite possible that at a fixed mass rate the heat transfer coefficient would increase with decreasing bed height due to earlier bed movement.

Effect of thermal Properties:

From theoretical consideration as well as from the data of fluidized beds (26, 27) it may be concluded that the thermal conductivity of the particles has no noticeable effect on heat transfer coefficients. The importance of particle heat capacity is clear from the particle movement in the bed (Fig. 15). Van Heerden et al. and Dow and Jakob have pioneered work towards an understanding of the importance of the heat capacity. Wen and Leva (30) also included the particle heat capacity in their generalized correlation for fluidized bed data although in the earlier correlation it was ignored.

Since air was the only spouting medium, it was not possible to examine the effect of gas thermal conductivity on heat transfer coefficients. In a fixed bed, it is found that $h \propto K_g^{0.67}$. Van Heerden and coworkers (28) found that $h \propto K_g^{0.5}$ in a fluidized bed. Jakob and Osberg (49) report a twenty-one fold range in thermal conductivity and ten fold range in particle diameter. Except for the very high region, their data also indicate that $h \propto K_g^{0.64}$.

The particle shape and bed void fraction are the known important factors that have not been investigated. Polyethylene-1 and 2 were cylindrical and polyethylene-3 was spherical. Wheat-1 and 2 were nearly spherical and wheat-3 and 4 were sized from crushed wheat. With so much variation of shape factor in the experimental condition, no noticeable effect of shape factor on heat transfer coefficient was observed.

The study of effect of bed porosity on heat transfer in a spouted bed is very difficult. Except for qualitative observations, bed porosity and its variation is not known as yet.

Now the question arises whether the mass velocity has any effect on bed porosity. It has been explained earlier that with the increase of mass velocity both the spout diameter and bed height increases. If the volumetric increment in both cases is the same, then the bed porosity may be independent of mass velocity.

CONCLUSION

1. Pressure drop and heat transfer data as well as visual observation of spouting phenomena show that a spouted bed has three distinct stages: (a) fixed bed, (b) transition bed, and (c) spouted bed; whereas in fluidized beds there are two stages: (a) fixed bed, and (b) fluidized bed.

2. Uniform temperature distribution is observed at the annulus all through the bed except near the wall.

3. Two resistances to heat transfer are in operation in parallel in spouted beds; one at the spout wall and the other at the column wall. The magnitude of the spout wall resistance decreases with bed level and that of the column wall increases.

4. The heat transfer coefficient increases with increase in mass velocity up to the point of spouting. After spouting, it is found to be independent of mass velocity within the experimental range.

5. In spouted beds, the heat transfer coefficient is 10 to 66% lower than the maximum heat transfer coefficient in fluidized beds.

6. The mass velocity for spouting varies from 35-55% of that required for obtaining maximum heat transfer in a fluidized bed.

7. The heat transfer coefficient in a spouted bed increases with particle diameter and in a fluidized bed it decreases.

8. The heat transfer coefficient is independent of column diameter and orifice diameter and decreases with bed height.

9. The experimental data for the spouted bed were correlated according to dimensional analysis to yield the equations:

$$\text{Polyethylene} \quad \frac{h D_p}{K_g} = 8.7 \left(\frac{D_p}{L} \right)^{0.17} \left(\frac{D_p^3 \rho_g^2 g}{\mu^2} \right)^{0.52}$$

$$\text{Rice} \quad \frac{h D_p}{K_g} = 8.2 \left(\frac{D_p}{L} \right)^{0.17} \left(\frac{D_p^3 \rho_g^2 g}{\mu^2} \right)^{0.52}$$

$$\text{Polystyrene} \quad \frac{h D_p}{K_g} = 6.3 \left(\frac{D_p}{L} \right)^{0.17} \left(\frac{D_p^3 \rho_g^2 g}{\mu^2} \right)^{0.52}$$

$$\text{Wheat} \quad \frac{h D_p}{K_g} = 7.7 \left(\frac{D_p}{L} \right)^{0.17} \left(\frac{D_p^3 \rho_g^2 g}{\mu^2} \right)^{0.52}$$

$$\text{For all solids} \quad \frac{h D_p}{K_g} = 0.54 \left(\frac{D_p}{L} \right)^{0.17} \left(\frac{D_p^3 \rho_g^2 g}{\mu^2} \right)^{0.52} \left(\frac{\rho_b c_s}{\rho_g c_g} \right)^{0.45} \left(\frac{\rho_g}{\rho_s} \right)^{0.08}$$

10. The transition bed data were also correlated according to the dimensional analysis to yield the equations:

$$\text{Polyethylene} \quad \frac{h D_p}{K_g} = 0.00019 \left(\frac{D_p G}{\mu} \right)^{2.8} \left(\frac{\mu^2}{D_p^3 \rho_g^2 g} \right)^{1.10}$$

$$\text{Polystyrene} \quad \frac{h D_p}{K_g} = 0.00014 \left(\frac{D_p G}{\mu} \right)^{2.8} \left(\frac{\mu^2}{D_p^3 \rho_g^2 g} \right)^{1.10}$$

$$\text{Wheat} \quad \frac{h D_p}{K_g} = 0.000165 \left(\frac{D_p G}{\mu} \right)^{2.8} \left(\frac{\mu^2}{D_p^3 \rho_g^2 g} \right)^{1.10}$$

For all solids

$$\frac{h D_p}{K_g} = 3.5 \times 10^{-5} \left(\frac{D_p G}{\mu} \right)^{2.8} \left(\frac{\mu^2}{D_p^3 \rho_g^2 g} \right)^{1.1} \left(\frac{\rho_b c_s}{\rho_g c_g} \right)^{0.43} \left(\frac{\rho_b}{\rho_g} \right)^{0.22}$$

APPENDIX

PRESSURE DROP

Introduction

For both theoretical and practical purposes, one would like to know the mass velocity required for spouting, maximum spoutable bed depth, the spout diameter, maximum and spouting pressure drop, and bed turnover. Some of the information available in the literature will be discussed later on. Information relating to pressure drop is very vital, but no attempt has been made as yet to find a generalized correlation. It is not the intention of the present undertaking to make a detailed study on pressure drop. Limited data were collected and an attempt is made to find a correlation for pressure drop.

Review

Previous work on 6, 9 and 12 (3) and 24-inch (50) columns resulted in an empirical equation for minimum spouting velocity.

$$U_m = \left(\frac{D_p}{D_c}\right) \left(\frac{D_i}{D_c}\right)^{1/3} \left[\frac{2 g L (\rho_b - \rho_f)}{\rho_f} \right]^{0.5} \quad (61)$$

For a 6-inch column and a cone angle range of 45 to 85°, the exponent n was found to be 1/3. For a column of 24 inch diameter, the exponent n was found to vary with cone angle. Thus, for orifice diameter ranging from 1 7/8 to 4 in., n = 0.23 for a cone of 45° and n = 0.13 for a cone of 85°. Further work (42) confirmed the value of n as 1/3 and the effect of cone angle on n was considered to be within experimental error. Buchanan and Mamurung (8) found that the variation of minimum spouting velocity with bed height was not in agreement with Mathur and Gishler's

equation. The deviation accounted for an error of ± 15 per cent for bed heights of between 0.75 and 4.0 feet. The authors are conducting further experiments to clarify this discrepancy. Leva (51) compared the minimum spouting velocity with minimum fluidization velocity and found a good relation between them. Becker (52) found that they are related as follows

$$V_m = 1.25 V_{mf} \quad (62)$$

For a given orifice diameter and column diameter, only a certain bed depth of packing could be spouted. Gishler and Mathur (53) in their American Patent gave the following tentative formula to predict the maximum spoutable bed depth

$$\frac{L_m^{0.7}}{D_p} = \phi \frac{L^{0.6}}{D_c} \quad (63)$$

Becker (52) proposed the following correlation for maximum spoutable bed depth

$$\left(\frac{L_m}{D_p}\right) \left(\frac{D_p}{D_c}\right)^{1.76} \left(22 + \frac{2600}{Re_m}\right) \left(12.2 \frac{D_1}{D_c}\right)^n (\lambda)^{2/3} Re_m^{1/3} = 42 \quad (64)$$

the value of n varying from 0 to 0.41. Maximum and spouting pressure drop for 6-in. full and semicircular columns have been correlated by Madonna and Lama (54), using Leva's (55) equation:

$$\frac{\Delta P}{L} = \frac{K}{Ec} \left(\frac{D_p G}{\mu}\right)^n \left(\frac{\mu^2}{\rho}\right) \left(\frac{\lambda^{3-2}}{D_p^3}\right) \left(\frac{1-\delta}{63}\right)^{3-n} \quad (65)$$

to give maximum pressure drop

$$\frac{\Delta P_{21}}{L} = 1120 \frac{G \mu \lambda^2 (1-\delta)^2}{D_p^2 \rho_g \epsilon_c \delta^3} \quad (66)$$

and spouting pressure drop

$$\frac{\Delta P_B}{L} = 7h \frac{G^{1.25} \mu^{0.75}}{\epsilon_c \rho_f} \left(\frac{\lambda}{D_p} \right)^{1.75} \frac{(1-\delta)^{1.75}}{\delta^3} \quad (67)$$

Experimental

The equipment used in this investigation was described under Part I. The materials used were polystyrene, polyethylene, millet, rice, barley, corn, flax seeds and wheat.

Additional data were collected from a 4-in. semicircular column with 60° cone and 1/2-in. orifice. Static pressures relative to atmospheric pressure were taken from water-filled vertical manometers. The manometers connected to 1/16-in. pressure taps were located about 1 inch above the orifice plate. To determine the pressure drop due to the solids alone, data were collected for the empty column at different flow rates.

Theoretical and correlation of data

No attempt will be made here to find a theory for pressure drop in the spouted bed since with the present knowledge it is not possible. A review of the theory of flow of non-adsorbable gases through

beds of different packings will be presented and the possibility of its application will be discussed.

All the factors affecting pressure drop in packed beds are not susceptible to a complete and an exact mathematical analysis. Various workers in the field have made simplifying assumptions or analogies so that they could utilize some of the general equations representing the forces exerted by the fluid in motion to arrive at a useful expression correlating these factors. Most authors agree that the variables that determine the pressure drop may be classified into two groups:

First: Variables related to the fluid passing the bed: (a) fluid mass velocity, (b) fluid density, and (c) fluid viscosity.

Second: Variables related to the character of the packed bed: (a) Voidage of the bed and particle orientation, (b) shape of the particles, (c) diameter of the particles and the vessels, and (d) surface roughness of the particles.

Kozeny (56) derived an equation for pressure drop by assuming that a granular bed is equivalent to a group of parallel similar channels, such that their total internal surface and total internal volume are equal to the particle surface and the void volume of the bed, respectively. Carman (57) proved the validity of the correlation of Kozeny and introduced the concept of shape factor. Leva and coworkers (55) followed an analysis similar to that of Kozeny and Carman derived the following equation from the equation of fluid flow in empty pipes.

$$\frac{\Delta P}{L} = \frac{K}{\epsilon c} \frac{D_p G}{\mu} \frac{\mu^2}{\rho_g} \frac{\lambda^{3-n}}{D_p^3} \frac{(1-\delta)^{3-n}}{\delta^3} \quad (68)$$

For completely laminar motion $n = 1$ and for completely turbulent condition $n = 2$.

Some authors consider the flow through the packed bed as orifice type. One part of a flow-path has a greater cross section than another; the flow path expands and contracts depending on the shape and relative position of the particles. Since restricted path offers a much greater resistance than a large one, the flow takes place principally through a relatively small number of larger channels.

Reynolds (58) was first to formulate the resistance offered by friction to the motion of the fluid as the sum of two terms, proportional respectively to the first power of the fluid velocity and to the product of the density of the fluid with second power of its velocity:

$$\Delta P/L = a U + b \rho U^2 \quad (69)$$

where ΔP is the pressure loss along the length L , ρ the density of fluid, U its linear velocity and a and b are factors which are functions of the system.

With equation (69) as a basis, Ergun (59) derived the following equation for pressure drop in a packed bed.

$$\frac{\Delta P}{L} \frac{D_p \epsilon c \rho_g \delta^3}{G^2 (1-\delta)} = \frac{150 (1-\delta)}{Re} + 1.75 \quad (70)$$

For calculating the pressure drop in a packed bed, equation (63) and (69) are most widely used. Undoubtedly the theoretical basis of equation (69) is more sound.

Now turning to spouted beds, one would like to find a basis for calculating the pressure drop. The pressure drop in a bed is highly sensitive to bed density. It has been explained earlier that after the formation of the internal spout, the bed density surrounding the spout changes considerably. During spouting, visual observation does not show any remarkable variation of the annulus density except at the two ends, but this is not enough to indicate the uniform bed density. As there is no way to find an equation at the moment, it was decided to test the experimental data with equation (63) since Madonna and Lama already correlated their data with Leva's equation.

Pressure drop for the transition period:

A plot of

$$\frac{\Delta P}{L} \text{ vs. } \frac{G \mu \lambda^2 (1-5)}{D_p^2 \rho_f \epsilon_c^3} \quad (71)$$

is shown in Fig. 27. It is found that the data of the 6-in. column fall on one line and those of the 4-in. column on a different line. In the same Figure, literature data for a 24-in. (52), and 6-in. full and semicircular columns (54) are plotted. The data of the 6-in. full column fall on the same line as the present data but those of 24-in. full and 6-in. semicircular columns fall on separate lines. The data of each column fall on separate lines, the slope being 2500, 1150, 900 and 750 for the 24-in., 6-in. full column, 6-in. and 4-in. semicircular

Fig. 27. Pressure drop in prespouted beds in different columns.
(Material = Wheat 1)

column, respectively. Different slopes for different columns strongly suggest that there must be some other factors affecting the pressure drop which have not been included in the equation (68). The data are further correlated in Fig. 28 by plotting the slope of different line from Fig. 27 against the corresponding column diameter. The equation of straight line is

$$K = 270 \sqrt{D_c} \quad (72)$$

In the plot, hydraulic diameter D_h has been used for semicircular columns and calculated from the relation

$$D_h = \frac{4 \times \text{cross-sectional area}}{\text{wetted perimeter}} \quad (73)$$

The values of hydraulic diameters for 6-in. and 4-in. semicircular columns are 3.67 in. and 2.56 in. respectively. Combining equation (71) and (72), a final equation for pressure drop is obtained:

$$\frac{\Delta P}{L} = \frac{470 \sqrt{D_c} G \lambda^2 (1-\phi)^2}{D_p^2 g_c \rho_f \phi^3} \quad (74)$$

and shown in Fig. 29. The dimension of $\Delta P/L$ is still maintained as lbs/(sq.ft.)/ft. by attributing suitable dimension to the proportionality constant. It is also noticeable that the data for particles smaller than 0.10 inch deviate from the correlation. The smaller the particle, the larger the deviation.

Fig. 28. Plot of K_1 proportionality constant and D_c column diameter.

Fig. 29. General correlation of pressure drop data for prespouted beds.

Spouted Bed

All the data, both literature (2,54) and experimental are plotted in Fig. 30 as

$$\frac{\Delta P}{L} \text{ vs } \frac{G^{1.25}}{E_c \rho} \left(\frac{\lambda}{D_p} \right)^{1.75} \frac{(1-\delta)^{1.75}}{\delta^3}$$

The slope of the line is evaluated by least square method and found to be 80. The final equation becomes

$$\frac{\Delta P}{L} = 80 \frac{G^{1.25}}{E_c \rho} \left(\frac{\lambda}{D_p} \right)^{1.75} \mu^{0.75} \frac{(1-\delta)^{1.75}}{\delta^3} \quad (75)$$

Equation (75) may be written as a modified form of Fanning equation

$$\frac{\Delta P}{L} = \frac{2 f_m G^2 \lambda^2 (1-\delta)^{1.75}}{E_c \rho_f D_p \delta^3} \quad (76)$$

The value of modified friction factor f_m may be calculated from the experimental data by using the equation:

$$f_m = \frac{\Delta P}{2L} \frac{D_p}{G^2} \frac{\rho}{\lambda^{1.75}} \frac{E_c}{(1-\delta)^{1.75}} \delta^3 \quad (77)$$

The modified friction factor f_m vs. modified Reynolds number are plotted in Fig. 31 and the equation of the straight line is found to be:

$$f_m = 40 \left(\frac{D_p G}{\mu} \right)^{-0.75} \quad (78)$$

In an empty column with increase of mass velocity, the flow becomes more turbulent and the slope of the line f_m vs. Re_m changes gradually. A constant slope for a variation of Reynolds number from Fig. 31 indicates that increased mass velocity during spouting does not change the flow pattern of air in the bed. But this is difficult to conceive that increase flow rate will not increase the turbulence. The probable explanation is that the pressure drop is primarily caused at the annulus, and the extra air supply passes through the spout without changing the flow pattern at the annulus.

Fig. 30 General correlation of pressure drop data for spouted beds.

Fig. 31. Friction factor -vs- modified Reynolds number for spouted beds.

ESTIMATION OF SPOUT DIAMETER IN A SPOUTED BED

Introduction

To understand the flow pattern of the fluid and solid and to calculate and correlate the heat, mass, and momentum transfer data, it is important to know the dimensions of the spout in the column. As spouting causes a variation in the effective amount of solids exposed to a given flow of gas, interpretations of data based solely on measured values of space velocity or superficial velocity may yield entirely spurious conclusions. It seems therefore desirable to develop a correlation for predicting the spout diameter by investigating spouting materials of diverse properties under various experimental conditions.

The diameter of the spout varies slightly from top to bottom of the bed. However, this variation does not follow any general pattern. It may increase, decrease or remain fairly constant along the bed height and in some cases it may flare out to a maximum half way up the bed.

Mathur and Gishler (3) and Thornley, Saunby, Mathur and Osberg (42) measured the spout diameters in semicircular columns of different sizes for wheat and assumed that the spout diameters at different bed levels in the semicircular columns were identical to those of the full columns. This assumption was justified by the observation (3) that the spout diameters at the bed top of full and semicircular columns were identical and that the variation in spout diameter along bed height was relatively small. In the present investigation, eight materials were studied in two semicircular columns using the same assumption. The

diameters of the two columns are 4 and 6 inches, respectively.

Experimental

The materials used in this study were polystyrene, polyethylene, millet, rice, barley, corn, flax seeds and wheat. The physical properties of these materials are listed in Table 1. Data were obtained from 4- and 6-inch semicircular columns with plexiglas fronts.

Different orifice diameters were used and their sizes are reported in Table 53. A 60° cone angle was employed in all cases. A schematic diagram of the 6-inch semicircular column is shown in Fig. 32.

Compressed air used for spouting was filtered and dried before passing through the columns. A rotameter was used for measuring the flow rate. Straightening vanes were placed in the approach pipe to the column.

The void fraction of the bed was calculated from the volume of the bed, the weight of the material in the bed and the absolute density of the material. The absolute density was measured by a pycnometer.

In this investigation, the spout diameters were measured at different bed levels and the observed variation in spout diameter along bed height is relatively small. Typical examples are given in Table 52. The spout diameter data reported in Table 53 are the average values. In this table, the mean deviations from the average values are also listed.

Correlation and Discussion

It is obvious in Table 53 that in all cases the spout diameters increase with the mass flow rate of the spouting medium, air.

When the values of the spout diameters for any tested materials obtained in a given column were plotted against the mass flow rate of air on a log-log paper, a linear relationship was obtained with an approximate slope of 0.50 in all cases as shown in Fig. 33. Hence

$$d_s = \alpha G^{0.50} \quad (1)$$

where d_s = spout diameter, inch

G = mass flow rate of air, lb/(hr.)(sq.ft.)

α = proportionality constant.

The evaluation of the quantity G is based on the cross-sectional area of the empty column.

Equation (1) permits the estimation of spout diameters for a material under various conditions in a given column when the value of α is available at one condition. The values of the proportionality constant α for different materials investigated may be summarized as follows: for polystyrene and polyethylene, the values of α for the 4- and the 6-inch semicircular columns are 0.040 and 0.060, respectively; and for the other materials, the corresponding values are 0.037 and 0.055, respectively. The α value for wheat in a 24-inch semicircular column (42) is 0.122. Therefore, in a given column, the spout diameters measured under various conditions are not only proportional to the square root of the quantity G , but the proportionality constant may be practically considered identical for all the materials tested. In other words, in spite of the differences in shape, size and density of the

materials, the bed depth, the bed density and the orifice diameter, if a correlation is made on the basis of same values of G , the spout diameter in a spouted bed would be identical for all the materials tested. This correlation is only valid, of course, under spouting conditions. The value of G used in the correlation should therefore be equal to or greater than the minimum spouting velocity. A method for estimating the minimum spouting velocity has been proposed by Mathur and Gishler (3).

Neglecting the small difference in the α values for different materials in a given column, the α values were further correlated with the column diameter d_c by plotting d_c against α on semilog paper (Fig. 34) and the following expression was obtained:

$$\log d_c = \log 1.85 + 8.71 \alpha \quad (2)$$

or

$$\alpha = 0.115 \log d_c - 0.031 \quad (3)$$

Substituting the value of α in Equation (1),

$$d_s = (0.115 \log d_c - 0.031) G^{0.5} \quad (4)$$

The results obtained by using Equation (4) compare satisfactorily with the experimental and the literature values in Fig. 35. The average deviation is found to be ± 6 per cent. This generalized equation, which requires only the mass flow rate of air and the column diameter as primary information, provides a simple method for estimating the spout diameter in a spouted bed under various conditions.

Fig. 32. Schematic diagram of a spouted bed.

Fig. 33 Effect of mass velocity on spout diameter in 4 in., 6 in., and 24 in. semi-circular column.

Fig. 34. Plot of column diameter, D_c and proportionality constant α

Fig. 35. D_s experimental and D_s calculated

NOMENCLATURE

A_w	=	wall area in contact with spouted bed, sq. ft.
A_s	=	spout surface area, sq. ft.
C_g	=	specific heat of air, BTU/(lb-mass)(°F)
C_s	=	specific heat of solid material, BTU/(lb-mass)(°F)
C_1 and C_2	=	constants
D_c	=	diameter of column, ft.
D_p	=	diameter of particle, ft.
D_s	=	diameter of spout, ft.
D_i	=	diameter of orifice, ft.
D_h	=	hydraulic diameter, ft.
G	=	mass velocity of air based on empty column, lb-mass/(hr)(sq.ft.)
h	=	heat transfer coefficient, BTU/(hr)(sq.ft.)(°F)
h_s	=	spout wall heat transfer coefficient BTU/(hr)(sq.ft.) (°F)
h_w	=	column wall heat transfer coefficient BTU/(hr) (sq.ft.)(°F)
h_1, h_2, h_3, h_4	=	heat transfer coefficient at section 1, 2, 3, 4 respectively. BTU/(hr)(sq.ft.)(°F)
I	=	current, amp.
K	=	thermal conductivity, BTU/(hr)(ft)(°F)
K_g	=	thermal conductivity of air, BTU/(hr)(ft)(°F)
K_s	=	thermal conductivity of solid material BTU/(hr)(ft)(°F)
K_b	=	thermal conductivity of bulk material BTU/(hr)(ft)(°F)

$K_1, K_2, \text{etc.}$	=	proportionality constant
ΔP	=	pressure drop, lbs/sq.ft.
L	=	bed height, ft.
L_m	=	maximum spoutable bed height
Q	=	rate of heat flow from the bed to the surrounding, BTU/hr.
Q_1, Q_2, Q_3, Q_4	=	rate of heat flow from section 1, 2, 3 and 4, respectively
Q_s	=	rate of heat flow from the spout to the annulus, BTU/hr.
R	=	resistance per unit length of heating element
r	=	radius of column, ft.
S	=	surface area of particle, sq. ft.
T	=	temperature °F
T_a	=	annulus temperature, °F
T_w	=	wall temperature, °F
$T_{w1}, T_{w2}, T_{w3}, T_{w4}$	=	wall temperature of section 1, 2, 3 and 4, respectively
T_s	=	spout temperature, °F
U_m	=	minimum fluid velocity for steady state spouting ft/sec.
U_{mf}	=	minimum velocity of fluidization, ft/sec.
a, b, c, d	=	constants exponents
$\gamma = K/C_p$	=	thermal diffusivity, sq.ft/hr.
μ	=	viscosity of air, lb-mass/(hr)(ft)

ρ_g	= density of air, lb-mass/(cu.ft.)
ρ_b	= bulk density of solid material, lb-mass/(cu.ft.)
ρ_s	= absolute density of solid material, lb-mass/cu.ft.
δ	= void fraction, no dimension
λ	= shape factor, no dimension
τ	= time, hr.
$J_0(a_n \ r)$	= Bessel function of order zero of the first kind
a_n	= roots of $J_0(a_n) = 0$
A_n	= constant

REFERENCES

1. Sittig, M., Chem. Eng. 60, 219 (1953).
2. Matheson, G.L., Herbst, W.A., and Holt, P.H., Ind. Eng. Chem. 41, 1099, (1949).
3. Mathur, K.B., and Gishler, P.E., A.I.Ch.E. Journal, 1, 157 (1955).
4. Malek, M.A., Madonna, L.A., and Lu, Benjamin C.-Y., Ind. Eng. Chem. Process Design and Development, 2, No. 1, 30 (1963).
5. Mathur, K.B. and Gishler, P.E., J. Appl. Chem. 5, 624 (1955).
6. Becker, H.A. and Sallan, H.R., Chem. Eng. Sci. 13, 97 (1960).
7. Cowan, C.B., Peterson, W.S. and Osberg, G.L., Pulp and Paper Mag. of Can. 58, 138 (1957).
8. Buchman, R.H. and Manurang, F., Brit. Chem. Eng. 6, 402 (1961).
9. Leva, M., "Fluidization", p. 178, McGraw-Hill Book Company, New York, 1959.
10. Colburn, A.P., Trans. A.I.Ch.E. 26, 166 (1931).
11. Leva, M., Ind. Eng. Chem. 39, 857 (1947).
12. Leva, M., Ind. Eng. Chem. 42, 2498 (1950).
13. Schumacher, R., Erdol und Kohle 5, 189 (1949).
14. Chu, Y.C. and Storrow, J.A., Chem. Eng. Sci. 1, 230 (1952).
15. Plautz, Donald A. and Johnstone, H.F., A.I.Ch.E. Journal I, 193 (1955).
16. Coberly, C.A. and Marshall, W.R., Chem. Eng. Prog. 47, 141 (1951).
17. Hanratty, T.J., Chem. Eng. Sci. 3, 209 (1954).
18. Calderbank, P.H. and Pogorski, L.A., Trans. Inst. Chem. Eng. (London) 35, 195 (1957).

19. Quinton, J.H. and Storow, J.A., Chem. Eng. Sci. 5, 245 (1956).
20. Yagi, S. and Kunii, D., A.I.Ch.E. Journal 6, 97 (1960).
21. Leva, M. and Grummer, M., Chem. Eng. Prog. 48, 307 (1952).
22. Leva, M., Grummer, M. and Weintraub, M., Chem. Eng. Prog. 45, 563 (1949).
23. Leva, M., Weintraub, M., Grummer, M., Pollichik, M. and Storch, H.H., U.S. Bur. Mines, Bull. 504, 64 (1951).
24. Mickley, H.S. and Trilling, C.A., Ind. Eng. Chem. 41, 1135 (1949).
25. Levenspiel, O. and Walton, J.S., Chem. Eng. Prog. Symp. Series No. 9, 50, 1 (1954).
26. Dow, W.M. and Jakob, M., Chem. Eng. Prog. 47, 637 (1951).
27. Van Heerden, C., Nobel, A.P.P. and Van Krevelen, D.W., Chem. Eng. Sci. 1, 51 (1951).
28. Van Heerden, C., Nobel, A.P.P. and Van Krevelen, D.W., Ind. Eng. Chem. 45, 1237 (1953).
29. Toomey, R.D. and Johnstone, H.F., Chem. Eng. Prog. Symp. Series 49, 51 (1949).
30. Wen, Chin Young and Leva, M., A.I.Ch.E. Journal 2, 482 (1956).
31. Wender, L. and Cooper, G.T., A.I.Ch.E. Journal 4, 15 (1958).
32. Klassen, J. and Gishler, P.E., Can. J. Chem. Eng. 36, 12 (1958).
33. Ghosh, B. and Osberg, G.L., Can. J. of Chem. Eng. 37, 205 (1959).
34. Kistler, S.S. and Caldwell, A.G., Ind. Eng. Chem. 26, 658 (1934).
35. Smith, W.R. and Wilkes, G.B., Ind. Eng. Chem. 36, 1111, (1944).
36. Carslaw, H.S. "The Mathematical Theory of the Conduction of Heat in Solids", Macmillan and Company Ltd., London, 1921.
37. Babbitt, J.D., Can. J. Research F. 23, 388 (1945).

38. Kunii, D. and Smith, J.M., A.I.Ch.E. Journal 6, 71 (1960).
39. Dallavalle, I.A. "Micromeritics," P. 165, Pitman Publishing Corp., New York, 1948.
40. Jakob, M., "Heat Transfer" Vol. I, P. 278, John Wiley and Sons, New York, 1949.
41. Ruedenberg, R., Elektrotech., Z, 46, 1344 (1925).
42. Thornley, B., Saunby, J.B., Mathur, K.B. and Osberg, G.L., Can. J. Chem. Eng. 37, 184 (1959).
43. Heertjes, P.M., de Boer, H.G.J. and Van Dorsser, A.A. de Hass, Chem. Eng. Sci. 2, 97 (1953).
44. Baerg, A., Klassen, J. and Gishler, P.E., Can. J. Res. F. 48, 287 (1950).
45. Leva, M., Weintraub, M., Grummer, M., Pouchik, M. and Storch, H.H., U.S. Bur. Mines, Bull. 504, P. 87, 1951.
46. Madonna, L.A., Lama, R.F. and Brisson, W.L., Brit. Chem. Eng. 6, 524, (1961).
47. Kramers, H., Chem. Eng. Sci. 1, 35 (1951).
48. Bartholomew, R.N. and Katz, D.I., Chem. Eng. Progr. Symp. Series 48, 3 (1952).
49. Jacob, A. and Osberg, G.L., Can. J. Chem. Eng. 35, 5 (1957).
50. Thornley, B., Mathur, K.B., Klassen, J. and Gishler, P.E. "The effect of design variables on flow characteristics in a spouted bed", N.R.C. of Canada, 1955.
51. Leva, M. "Fluidization" p. 174, McGraw-Hill Book Co., New York, 1959.

52. Becker, H.A., Chem. Eng. Sci. 13, 245 (1961).
53. Gishler, P.E. and Mathur, K.B., U.S. Patent 2, 786, 250, March 26, 1957.
54. Madonna, L.A. and Lema, R.F., Ind. Eng. Chem. 52, 169 (1960).
55. - Ieva, M., Weintraub, M., Grummer, M., Pollichik, M. and Storch, H.H., U.S. Bur. Mines, Bull. 504, P. 8, 1951.
56. Kozery, J., Sitzber, Akad. Wiss. Wien, Math-naturw. Kl (Abt. 11a) 136, 271, (1927).
57. Carman, P.C., Trans. Inst. Chem. Eng. (London) 15, 150 (1937).
58. Reynolds, O. "Papers on Mechanical and Physical Subjects" Cambridge University Press, 1900.
59. Ergun, S., Chem. Eng. Prog. 48, 89 (1952).

SAMPLE CALCULATION FOR THERMAL CONDUCTIVITY AND SPECIFIC HEAT

Material: wheat

$$Q = 19.258 \text{ BTU/hr.}$$

$$C_1 = -26.054 \text{ (from Fig. 5)}$$

$$K = \frac{Q}{2 L C} = \frac{19.258}{8.381 \times 26.054} = 0.088 \text{ BTU/hr.ft.}^\circ\text{F.}$$

To calculate thermal diffusivity

$$A_n = \frac{B \frac{a}{\alpha_n} J_1(\alpha_n a) + C_1 \frac{a}{\alpha_n} J_1(\alpha_n a) \ln a - \frac{1}{\alpha_n^2}}{\frac{a^2}{2} J_1(\alpha_n a)^2}$$

from equation (27).

From Fig. 5,

$$C_1 = -26.054, \quad C_2 = 34.8, \quad a = 3.802'' \quad \log_e a = 1.336$$

From Table 54

$$J_1(\alpha_1 a) = 0.5191$$

$$J_0(\alpha_1 a) = 2.4048$$

$$\alpha = \frac{2.4048}{3.8020} = 0.6325$$

$$\text{Therefore } A_1 = \frac{\frac{34.8 \times 3.802}{0.6325} \times 0.5191 + (-26.054) \frac{3.8020}{0.6325} \times 0.5191 \times 1.3360 - \frac{1}{(6325)}}{\frac{(3.8020)^2}{2} (0.5191)^2}$$

$$= \frac{108.5880 - 26.0540 \times 1.6690}{1.9478} = \frac{65.1039}{1.9478} = 33.4293$$

Similarly the value of A_n up to 10 terms were calculated and shown in Table 51.

At position two, i.e. at radius .65", the temperature after 10 hours was 44.33°F and the equilibrium temperature was 46.0°F above room temperature. From equation (10),

$$t = T - \left[A_1 J_0 (a_1 r_2) e^{-a_1^2 \gamma T} + A_2 J_0 (a_2 r_2) e^{-a_2^2 \gamma T} + \dots \right]$$

or

$$44.33 = 46.5 - \left[33.4248 (a_1 r) e^{-a_1^2 \gamma T} + 14.754450 (a_2 r) e^{-a_2^2 \gamma T} + \dots \right] \quad (1)$$

Now

$$J_0 (a_1 r_2) = J_0 (0.6325 \times 0.65) = J_0 (0.4110)$$

and the corresponding value of $J_0 = 0.9582135$.

Therefore,

$$2.17 = 33.424 \times 0.9582135 e^{-(0.6325)^2 \times 360008 \gamma}$$

(neglecting the other terms)

$$= 32.027 e^{-14402.0 \gamma}$$

$$\text{Solving } \gamma = 0.000187 \text{ in}^2/\text{sec.}$$

The value of thermal diffusivity of different materials was calculated by using the following experimental data.

Material	Time hr.	t-T					
		Radius					
		0.15"	0.65"	1.15"	1.65"	2.15"	2.65"
Wheat	10	1.0	2.3	1.8	2.1	2.5	1.7
Corn	10	5.0	4.5	4.0	3.5	3.0	2.1
Polyethylene	10	4.0	3.3	3.0	3.0	2.2	1.7
Polystyrene	8	1.7	1.7	1.3	1.5	1.0	0.0
Flax Seeds	10	7.7	5.0	4.6	3.8	3.1	2.3
Millet	8	0.3	3.3	3.0	2.7	2.3	1.6
Barley	10	3.4	4.6	3.9	3.7	9.6	1.8
Rice	10	2.3	5.3	3.3	4.7	2.7	2.2
Sunflower	8	1.0	4.1	3.5	3.0	2.5	2.1
Timothy	10	13.7	12.3	7.3	6.3	3.7	2.0
Wood chips	10	1.0	1.0	0.2	1.5	0.7	0.0

Once the thermal conductivity, thermal diffusivity and bulk density were known, it was easy to calculate the specific heat from the relation:

$$C_p = \frac{K}{\gamma \rho}$$

$$= \frac{0.038}{0.00187 \times 25 \times 53.98} = 0.354$$

TABLES 4 - 10

Temperature distribution in a 6-in. column,
13-in. bed height and 3/4-in. orifice.

Material: Polyethylene-2

TABLE 4. Temperature Distribution in 6-in. Column, Run 13

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
0.0	160.70	160.30	159.70	157.67	157.00	153.00
0.06	155.30					
0.13	153.00					
0.25	149.70	160.00				
0.36	147.33					
0.50	146.33	159.67	159.0			
0.63	144.67					
1.00	127.67	155.00	155.70	149.70	149.70	143.00
1.13	110.67					
1.25	98.67					
1.50		144.67		139.70	137.00	131.00
1.63						
1.75						

....cont.

TABLE 4. (continued)

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
2.00		118.00	133.00	118.70	118.70	112.30
2.13						
2.25		102.00	119.00	105.33	106.00	102.00
2.38		93.00				
2.50			103.70	94.00	98.67	90.70
2.56		83.00				
2.63						
2.75			88.70	83.70	84.70	83.00
2.88			81.30	79.70	79.00	79.70
3.00			77.33	77.33	77.33	77.33

TABLE 5. Temperature Distribution in Full Column, Run 14

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
0.0	196.00	196.00	196.00	194.70	193.00	190.70
0.06						
0.13	189.67					
0.25	183.70					
0.38	182.70					
0.50	182.00	194.70				
0.63	180.00					
1.00	161.67	192.00	193.00	188.00	186.33	182.33
1.13	137.67					
1.25	115.70					
1.50		182.00		177.70	174.70	169.70
1.63						
1.75				166.33	165.00	159.70
2.00		158.33	167.70	155.67	151.30	143.00
2.13						

....cont.

TABLE 5. (continued)

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
2.25	130.33		150.70	132.00	129.33	126.00
2.38	118.33					
2.50	100.00		126.00	109.00	109.33	103.00
2.56	95.00					
2.63				100.30	98.70	
2.75			98.70	91.70	93.00	94.00
2.88			85.30	84.70	84.70	88.33
3.00			83.00	83.00	83.00	82.00

TABLE 6. Temperature Distribution in Full Column, Run 15

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
0.0	159.70	189.70	159.33	189.00	168.7	183.0
0.06						
0.13	103.67					
0.19						
0.25	178.66					
0.31						
0.38	180.30					
0.50	181.33	189.00				
0.63	179.70					
0.75	175.67					
0.90						
1.00	155.67	186.30	157.70	186.33	165.30	183.70
1.13	139.67					
1.25	117.33					

.....cont.

TABLE 6. (continued)

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
1.50	131.70	184.33	179.67	177.33	174.30	
1.88						
2.00	159.00	171.33	159.70	159.00	150.30	
2.25	136.00	154.33	139.33	139.70	132.70	
2.38	119.00					
2.50	103.00	131.00	114.33	113.70	114.70	
2.56	96.00					
2.63		115.67	105.00	103.3		
2.75		101.00	97.70	98.00	98.30	
2.88		88.33	90.0	89.0	90.00	
3.00		84.67	85.5	83.70	84.33	

TABLE 7. Temperature Distribution in Full Column, Run 16

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
0.0	187.00	183.0	171.30	163.00	162.70	162.67
0.063						
0.13	180.30	180.3				
0.25	173.00	178.0	169.70			
0.31	169.70					
0.38	166.00	174.7				
0.50	159.70	172.3	166.70			
0.63						
0.75	143.00	167.7				
0.88	136.00					
1.00	126.70	165.0	164.33	163.00	162.70	162.67
1.13	115.70					
1.25	109.0					

....cont.

TABLE 7. (continued)

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
1.50	163.70		163.33	163.70		
1.75						
2.00	158.00		172.67	159.67	157.30	152.00
2.25	143.70		160.00	153.67		140.30
2.38	127.00					
2.50	107.30		153.00	136.00	131.00	123.30
2.56	100.00					
2.63			144.00	127.00	121.30	1
2.75			125.33	117.33	110.00	103.70
2.88			105.33	104.30	100.00	96.50
3.00			95.00	96.00	90.00	91.70

TABLE 8. Temperature Distribution in Full Column, Run 17

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
0.0	187.00	178.33	165.30	143.70	145.3	142.0
0.06						
0.13	176.70	174.70	161.70	146.30		
0.25	162.30	169.00	157.00	145.00	143.0	
0.31	146.30					
0.38	139.0	163.33	152.0	143.0		
0.50	131.33	157.33	147.3	142.3	141.7	
0.63			144.70			
0.75	122.33	147.33	143.00			
0.88	118.00		141.70			
1.00	113.70	141.70	141.30	141.0	141.3	141.0
1.13	107.33					
1.25	102.70					

.....cont.

TABLE 8. (continued)

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
1.50		139.70				
1.75						
2.00		130.70	140.00	140.7	140.70	140.70
2.25		119.00	137.70	139.7		
2.38		110.70				
2.50		100.30	131.0	135.3	136.0	137.70
2.56		95.00				
2.63			124.0			135.30
2.75			115.0	124.0	124.0	131.0
2.88			102.0	111.70	112.30	121.0
3.00			95.0	100.30	98.70	100.7

TABLE 9. Temperature Distribution in Full Column, Run 19

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
0.00	188.3	178.7	167.7	150.3	147.0	143.0
0.06						
0.13	179.7	175.3		147.7	144.0	
0.25	167.3	170.7	159.7	145.30		
0.31	156.3					
0.38	144.0	165.0				
0.50	134.3	158.0	149.7	143.0		
0.63						
0.75	125.0	148.0	144.0			
0.88						
1.00	115.7	143.0	143.0	142.3	142.3	143.0
1.13	109.0					
1.25	102.7					

....cont.

TABLE 9. (continued)

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
1.50		139.7				
1.75						
2.00		131.3	141.7	141.7	142.0	142.0
2.25		122.7	139.7			141.7
2.38		113.7				
2.50		103.3	132.3	137.3	139.0	140.3
2.56		99.3				
2.63					135.3	138.5
2.75			119.0	126.7	129.7	134.7
2.88			107.3	116.0	119.0	125.0
3.00			99.70	102.0	108.0	110.0

TABLE 10. Temperature Distribution in Full Column, Run 22

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
0.00	188.3	180.30	163.33	153.3	149.0	144.7
0.06			166.30			
0.13	173.70	176.30	164.30			
0.25	165.70	171.00	160.70			
0.31	153.0		157.7			
0.38	143.0	165.70	155.0			
0.50	134.0	160.0	149.7	144.0	143.0	143.0
0.63			146.0			
0.75	126.00	149.30	143.3			
0.88						
1.00	117.3	143.0	142.0	143.0	143.0	143.0
1.13	111.0					
1.25	105.30					

....cont.

TABLE 10 (continued)

Distance in inches from centre	T E M P E R A T U R E					
	SECTION 1		SECTION 2		SECTION 3	
	Position 1	Position 2	Position 1	Position 2	Position 1	Position 2
1.50		139.70				
1.75						
2.00		131.30	140.70	142.7	142.70	142.70
2.25		122.70	137.30			
2.38		113.70				
2.50		102.0	131.30	137.30	139.70	140.70
2.56		98.70				
2.63			126.0			138.0
2.75			117.7	127.7	131.0	134.7
2.88			105.0	115.3	120.70	125.0
3.00			98.0	100.0	110.3	109.0

TABLES 11 - 17

Heat transfer data from a 6-in. column,
13-in. bed height, 3/4-in. orifice

TABLE 11. 6-in. Column, 13-In. bed height, 3/4-in. orifice

Material: Wheat-1

Run No.	G	$D_p G / \mu$	h_2	h_3	$h_{av.}$	$\frac{h D_p}{K_E}$	T_2	T_3	T_{w2}	T_{w3}	Q_2	Q_3
1	114.6	33.5	3.0	3.1	3.1	2.4	166.0	162.8	65.0	64.3	143.6	145.0
2	229.2	66.9	3.7	3.8	3.8	3.0	175.8	174.2	72.0	70.8	182.4	186.6
3	343.8	100.4	5.1	5.1	5.1	4.0	169.7	169.0	74.7	75.0	230.1	227.7
4	458.4	133.9	6.8	6.1	6.5	5.0	163.7	163.0	74.3	74.3	288.8	257.0
5	573.0	167.3	10.9	7.9	9.4	7.2	161.5	161.5	80.0	80.5	422.0	304.0
6	641.8	187.4	14.5	12.1	13.3	10.2	153.8	149.7	88.4	87.8	450.4	355.8
7	687.6	200.8	17.2	15.2	16.2	12.3	144.2	135.0	88.3	88.3	456.7	337.2
8	802.1	234.2	18.8	20.0	19.4	15.1	132.6	133.6	89.0	89.0	389.3	423.7
9	870.9	254.3	20.9	21.8	21.4	16.5	137.7	137.7	90.5	90.0	468.6	494.0
10	916.7	267.7	19.2	22.0	21.6	15.0	138.0	138.0	91.5	91.5	440.2	485.9
11	962.6	281.1	20.5	22.5	21.5	16.7	140.0	140.3	93.3	93.0	454.8	505.5
12	1031.3	301.1	20.0	21.8	20.9	15.9	141.0	141.0	94.3	94.2	443.7	483.6

TABLE 12. 6-in. Column, 13-in. bed height, 3/4-in. orifice

Material: Polyethylene-2

Run No.	G	D _p G/μ	h ₂	h ₃	h _{av.}	$\frac{hD_p}{K_g}$	T ₂	T ₃	T _{w2}	T _{w3}	Q ₂	Q ₃
13	114.6	26.3	2.3	2.3	2.3	1.4	158.7	155.0	77.3	76.7	85.1	35.5
14	229.2	52.6	3.3	2.8	3.1	1.9	195.4	191.9	83.0	83.0	176.2	144.8
15	343.8	73.9	4.2	3.8	4.0	2.5	189.2	188.3	84.7	84.5	208.5	191.0
16.	458.4	106.2	10.1	7.5	8.8	5.4	167.2	162.7	97.3	97.0	337.0	234.1
17	500.0	115.8	13.2	12.8	13.0	8.0	163.8	154.3	97.3	97.3	417.0	407.4
18	573.0	132.7	18.3	19.8	19.1	11.9	141.0	141.0	96.5	97.0	386.8	413.8
19	618.3	143.1	20.6	21.7	21.2	13.1	142.5	142.5	97.0	97.0	445.3	471.2
20	641.7	148.6	20.6	21.5	21.3	13.1	145.0	144.3	99.3	98.8	447.2	464.7
21	687.6	159.3	20.8	21.8	21.3	13.1	142.8	142.4	98.7	99.0	435.7	449.4
22	733.4	169.9	20.5	21.7	21.1	13.0	145.7	145.0	98.3	99.0	447.9	461.0
23	825.1	191.1	20.5	21.7	21.1	13.0	142.5	143.0	100.0	100.5	413.8	426.0

TABLE 13. 6-in. column, 13-in. bed height, 3/4 in. orifice

Material: Polyethylene-3

Run No.	G	$\frac{DpO}{\mu}$	h ₂	h ₃	h _{av.}	$\frac{hDp}{Kg}$
24	114.6	11.7	2.2	2.0	2.1	0.6
25	229.2	23.5	3.8	2.6	3.2	1.0
26	266.2	27.3	7.5	6.5	7.0	1.9
27	300.0	30.7	11.3	11.7	11.5	3.1
28	343.8	35.2	12.9	14.3	13.6	3.7
30	389.6	39.9	12.4	13.8	13.1	3.6
31	412.5	42.3	12.4	13.6	13.0	3.5
32	504.2	51.6	13.1	14.1	13.6	3.7
33	573.0	58.7	12.7	14.7	13.7	3.7

TABLE 14. 6-in. column, 13-in. bed height, 3/4 in. orifice

Material: Polyethylene-1

Run No.	G	D _p G/μ	h ₂	h ₃	h _{av.}	$\frac{hD_p}{Kg}$	T ₂	T ₃	T _{w2}	T _{w3}	Q ₂	Q ₃
34	114.6	30.2	3.1	3.0	3.1	2.7	142.0	137.8	60.0	59.5	120.9	111.6
35	229.2	60.5	4.2	3.7	4.0	3.1	152.0	152.0	62.0	62.7	179.6	156.9
36	343.8	90.7	5.6	4.5	5.1	4.0	154.2	153.7	67.0	66.7	232.0	186.0
37	458.2	121.0	8.0	6.7	7.4	5.2	153.0	152.3	78.3	78.3	283.9	235.5
38	573.0	151.2	15.6	12.7	13.4	9.7	141.4	136.7	83.0	82.0	432.7	330.0
39	618.8	163.3	17.6	17.3	17.5	12.3	139.3	131.3	76.3	76.7	526.7	443.7
40	687.6	181.5	21.4	22.5	22.0	15.5	121.0	120.3	78.0	78.0	437.1	452.1
41	733.4	193.5	19.8	23.7	21.7	15.0	131.0	130.2	80.5	80.5	475.0	512.3
43	802.1	211.7	20.6	23.4	22.0	15.8	125.0	126.0	81.3	81.3	437.4	467.1
45	916.9	242.0	21.8	22.9	22.4	15.5	128.0	127.3	75.0	75.0	543.8	556.5

TABLE 15. 6-in. column, 13-in. bed height, 3/4 in. orifice

Material: Polystyrene-1

Run No.	G	$D_p G/\mu$	h_2	h_3	$h_{av.}$	$\frac{hD_p}{K_g}$	T_2	T_3	T_{w2}	T_{w3}	Q_2	Q_3
46	114.6	28.1	2.2	2.1	2.2	1.5	141.0	139.8	54.0	53.5	90.9	86.1
47	229.2	56.2	3.7	3.2	3.5	2.3	151.3	150.8	59.0	58.3	162.2	140.6
48	343.8	84.3	4.5	3.5	4.0	2.6	145.0	145.0	60.0	59.5	181.7	142.1
49	458.4	112.4	7.3	4.5	5.9	3.9	154.3	154.3	67.0	67.3	302.7	186.0
50	573.0	140.5	11.3	9.4	10.4	6.9	144.7	143.7	71.7	70.8	391.8	326.4
51	618.8	151.7	12.9	13.1	13.0	8.6	140.3	132.3	71.7	72.7	420.3	370.9
52	637.6	168.5	16.0	17.4	16.7	11.1	121.5	120.6	71.0	72.7	383.8	395.9
53	710.5	174.2	15.8	17.3	16.6	11.0	122.0	121.3	70.3	70.5	333.0	415.0
54	733.4	179.8	16.2	16.7	16.1	10.7	122.3	122.3	71.7	72.3	389.4	396.6
55	756.3	185.4	16.3	17.8	17.1	11.3	126.0	125.6	71.0	70.8	425.8	462.3
56	802.1	196.6	16.0	17.5	16.8	11.1	122.5	121.0	71.7	72.0	326.1	407.3
57	916.7	224.7	15.9	16.9	16.4	11.1	124.5	124.5	72.3	72.3	394.2	419.0

111

TABLE 16. 6-in. column, 13-in. bed height, 3/4 in. orifice

Material: Polystyrene-2

Run No.	G	D _{PG} /μ	h ₂	h ₃	h _{av.}	$\frac{hDp}{Kg}$	T ₂	T ₃	Tw ₂	Tw ₃	Q ₂	Q ₃
58	114.6	13.8	2.0	1.9	2.0	0.6	134.0	134.0	54.7	54.0	75.3	72.2
59	229.2	27.6	3.2	2.8	3.0	0.9	153.0	152.5	59.3	58.7	142.4	124.7
60	300.0	36.1	5.9	6.1	6.0	1.9	126.7	115.2	57.3	58.0	194.5	165.7
61	343.8	41.4	8.2	8.3	8.3	2.7	114.0	113.5	59.3	60.0	213.0	210.9
62	389.6	46.9	9.9	11.0	10.5	3.4	113.7	113.5	58.7	58.7	258.6	286.3
64	435.5	52.4	10.2	11.8	11.0	3.5	107.0	107.0	59.7	59.0	229.2	269.0
66	504.2	60.7	9.9	11.0	10.5	3.4	110.3	110.0	60.0	60.0	235.1	266.5

TABLE 17. 6-in. column, 13-in. bed height, 3/4 in. orifice

Material: Polystyrene-3

Run No.	G	D _p G/μ	h ₂	h ₃	h _{av.}	$\frac{hD_p}{Kg}$	T ₂	T ₃	T _{w2}	T _{w3}	Q ₂	Q ₃
67	504.2	103.9	14.6	16.0	15.2	8.4	120.3	120.0	68.5	68.5	359.2	391.4
68	550.1	113.4	15.0	16.2	15.6	8.6	123.7	123.7	67.2	67.0	401.9	436.3
70	641.8	132.4	14.3	17.0	15.7	8.5	122.0	121.5	69.7	69.7	355.2	418.3

TABLES 18 - 31

Heat transfer data for a 6-in. column,
9-in., 13-in. and 18-in. bed heights
and 1/2-in. orifice

TABLE 18. 6-in. column, 1/2-in. orifice

Material: Polyethylene-1

Run No.	G	$\frac{SpG}{\mu}$	Bed height in inch	h_2	h_3	h_4	$h_{av.}$	$\frac{hD_p}{kg}$	T_a	T_{w2}	T_{w3}	T_{w4}	Q_2	Q_3	Q_4
71	699.1	184.5	18	19.6	20.4	23.0	21.2	14.9	120.7	87.7	87.3	88.3	307.2	323.6	433.1
72	802.2	211.7	18	18.9	20.7	22.9	21.1	14.8	125.6	91.0	91.0	91.0	310.6	340.2	519.0
73	643.0	223.8	18	19.2	20.7	22.9	21.2	14.9	123.7	89.5	89.5	89.0	311.9	336.3	520.5
74	573.0	151.2	13	21.0	22.8		21.9	15.4	125.7	89.7	89.7		359.1	389.9	
75	733.4	193.5	13	20.0	22.5		21.3	15.0	124.5	90.3	90.0		325.1	368.7	
76	453.4	121.0	9	23.3			23.3	16.4	128.3	91.7			405.1		
77	595.9	157.2	9	22.9			22.9	16.1	127.5	89.7			422.0		

TABLE 19. 6-in. column, 1/2-in. orifice

Material: Polyethylene-2

Run No.	G	$\frac{D \cdot G}{\mu}$	Bed height in inch	h_2	h_3	h_4	$h_{av.}$	$\frac{hD}{K_g}$	T_a	T_{w2}	T_{w3}	T_{w4}	Q_2	Q_3	Q_4
78	618.3	143.2	18	17.5	19.8	21.9	20.0	12.3	115.7	34.7	34.7	34.0	257.5	291.6	454.7
79	733.4	169.8	18	16.9	18.8	21.1	19.2	11.3	119.0	33.5	33.5	83.5	235.0	317.0	490.7
80	504.2	116.8	13	20.3	21.5		20.8	12.8	127.7	34.7	34.0		444.6	446.3	
81	641.8	148.7	13	19.9	21.3		20.6	12.7	119.0	36.5	86.5		307.2	328.8	
82	412.5	95.5	9	22.5			22.5	13.9	122.7	35.3			399.7		
83	550.1	127.4	9	21.8			21.8	13.5	120.3	34.0			375.9		

TABLE 20. 6-in. column, 1/2-in. orifice

Material: Polyethylene-3

Run No.	G	$\frac{D_p C}{\mu}$	Bed height in inch	k ₂	h ₃	h ₄	h _{av.}	$\frac{h D_p^2}{K g}$	T _a	T _{w2}	T _{w3}	T _{w4}	Q ₂	Q ₃	Q ₄
84	295.0	30.2	13	10.9	12.6	13.8	12.6	3.4	116.0	33.3	33.0	33.0	169.3	197.5	293.3
85	435.5	44.6	18	11.0	13.3	14.1	13.0	3.5	119.5	36.0	36.7	36.7	171.4	207.2	285.7
86	250.2	25.6	13	12.8	14.8		13.8	3.8	120.7	31.7	31.0		237.1	279.1	
87	339.6	32.9	13	13.4	15.2		14.1	3.8	120.3	32.3	32.7		178.2	271.5	
88	207.9	21.3	9	14.4			14.4	3.9	115.0	30.7			234.6		
89	320.9	32.9	9	13.8			13.8	3.8	118.3	79.3			255.6		

TABLE 21. 6-in. column, 1/2-in. orifice

Material: Polystyrene-1

Run No.	G	$\frac{DpG}{\mu}$	Bed height in inch	h ₂	h ₃	h ₄	h _{av.}	$\frac{hDp}{K_g}$	T _a	T _{w2}	T _{w3}	T _{w4}	Q ₂	Q ₃	Q ₄
90	710.5	711.2	18	13.6	15.5	17.8	15.9	10.4	126.0	85.7	85.3	86.0	260.3	299.6	469.0
91	825.1	202.2	18	12.9	15.0	16.8	15.1	9.9	120.7	83.0	83.0	83.0	231.0	268.6	411.9
92	573.0	140.5	13	15.9	13.7		16.6	10.8	130.0	83.3	88.3		390.5	424.8	
93	637.6	168.5	13	14.5	17.6		16.1	10.5	129.5	87.3	87.0		290.7	255.3	
94	467.0	114.5	9	17.2			17.2	11.2	129.0	86.5			347.2		
95	595.9	146.1	9	16.0			16.0	10.4	128.5	87.0			314.6		

TABLE 22. 6-in. column, 1/2-in. orifice

Material: Polystyrene-2

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h_2	h_3	h_4	$h_{av.}$	$\frac{h D_p}{K_g}$	T_a	T_{w2}	T_{w3}	T_{w4}	Q_2	Q_3	Q_4
96	342.8	41.4	18	8.6	9.4	11.6	10.1	3.2	117.3	88.0	88.0	88.0	119.7	130.8	222.6
97	389.6	46.9	18	8.7	9.8	11.0	10.3	3.3	113.0	85.0	85.0	85.3	115.7	130.3	199.6
98	325.0	39.1	13	9.4	11.8		10.6	3.4	116.3	84.7	84.3		141.1	179.4	
99	389.6	46.9	13	9.5	11.5		10.5	3.4	114.7	85.3	85.0		132.7	162.3	
100	275.0	33.1	9	9.8			9.8	3.1	113.0	82.3			166.2		
101	366.7	44.2	9	10.6			10.6	3.4	117.5	82.7			175.2		

TABLE 23. 6-in. column, 1/2-in. orifice

Material: Polystyrene-3

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h ₂	h ₃	h ₄	$\bar{h}_{av.}$	$\frac{h D_p}{K_g}$	T _a	Tw ₂	Tw ₃	Tw ₄	Q ₂	Q ₃	Q ₄
102	606.0	125.0	18	12.7	14.3	16.6	14.5	8.0	118.3	83.3	83.0	83.3	211.1	239.8	330.6
103	802.1	165.4	18	11.8	14.5	15.5	13.9	7.6	118.0	80.5	80.5	80.5	210.2	258.3	380.6
104	515.0	106.2	13	14.5	16.4	-	15.5	8.5	120.5	80.5	80.5	-	275.5	211.6	-
105	641.7	132.3	13	14.8	15.9	-	15.4	8.5	121.3	81.3	81.3	-	231.2	302.1	-
106	428.0	38.3	9	15.8	-	-	15.8	8.7	115.7	81.0	-	-	260.4	-	-
107	458.4	94.5	9	16.2	-	-	16.2	8.9	115.7	81.0	-	-	267.0	-	-

TABLE 24. 6-in. column, 1/2-in. orifice

Material: Wheat-1

Run No.	G	$\frac{P}{\mu}$	Bed height in inch	b ₂	h ₃	b ₄	h _{av.}	$\frac{hD_p}{K_g}$	T _a	T _{w2}	T _{w3}	T _{w4}	Q ₂	Q ₃	Q ₄
103	843.0	217.6	18	18.2	21.0	22.0	20.8	16.2	129.3	95.5	95.0	96.4	292.2	351.6	474.1
109	962.6	281.1	18	19.3	19.4	21.9	20.2	15.7	133.0	94.5	94.0	94.3	353.0	359.4	555.1
110	802.1	234.2	13	20.8	22.4		21.6	16.8	132.7	98.7	98.7		335.9	361.8	
111	916.8	267.7	13	20.3	21.8		21.1	16.4	131.0	98.0	98.0		313.2	341.7	
112	630.3	184.1	9	21.9			21.9	17.0	136.0	98.7			383.0		
113	802.2	234.3	9	21.9			21.9	17.0	135.3	97.3			395.3		

TABLE 25. 6-in. column, 1/2-in. orifice

Material: Wheat-2

Run No.	G	$\frac{DpG}{\mu}$	Bed height in inch	h ₂	h ₃	h ₄	h _{av.}	$\frac{hDp}{K_g}$	T _a	Tw ₂	Tw ₃	Tw ₄	Q ₂	Q ₃	Q ₄
114	820.0	227.6	18	16.6	18.9	20.1	18.5	13.7	111.7	87.3	87.0	87.6	192.4	221.7	484.4
115	916.8	254.5	18	15.9	18.2	19.9	18.0	13.3	112.3	85.3	85.3	85.7	204.0	233.5	352.2
116	767.8	213.1	13	18.3	20.8		19.6	14.5	136.0	101.7	101.7		298.1	338.8	
117	848.0	235.4	13	18.5	21.2		19.8	14.6	135.3	100.7	100.3		304.1	352.6	
118	573.0	159.0	9	20.5			20.5	15.2	122.7	90.7			311.6		
119	637.6	190.9	9	21.6			21.6	16.0	121.3	91.0			310.8		

TABLE 26. 6-in. column, 1/2-in. orifice

Material: Wheat-3

Run No.	G	$\frac{n_p}{\mu}$	Bed height in inch	h_2	h_3	h_4	$h_{av.}$	$\frac{hD}{K_g}$	T_a	Tw_2	Tw_3	Tw_4	Q_2	Q_3	Q_4
120	385.0	54.0	18	11.1	11.2	14.9	12.6	4.7	106.3	84.3	84.0	85.3	126.5	129.2	224.5
121	504.2	70.8	18	10.9	11.2	15.0	12.4	4.6	111.7	87.6	87.6	87.6	124.8	128.2	236.9
122	332.3	46.6	13	12.6	15.0		13.8	5.2	118.7	90.7	91.0		167.6	197.4	
123	458.4	64.3	13	13.0	14.5		13.8	5.2	118.0	90.3	91.0		171.1	186.0	
124	240.6	33.8	9	14.8			14.8	5.5	106.3	83.0			163.8		
125	366.7	51.5	9	15.2			15.2	5.7	108.5	83.7			179.1		

TABLE 27. 6-in. column, 1/2-in. orifice

Material: Wheat-4

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h_2	h_3	h_4	$h_{av.}$	$\frac{h \Delta p}{K_g}$	T_a	T_{w2}	T_{w3}	T_{w4}	Q_2	Q_3	Q_4
126	309.4	30.7	18	8.9	10.4	12.2	10.7	2.8	103.3	85.7	85.7	85.7	95.5	111.6	180.6
127	412.6	41.0	18	9.1	10.5	12.5	10.7	2.8	107.3	84.6	84.0	84.6	98.1	116.2	185.9
128	224.6	22.3	13	10.3	12.9		11.6	3.1	103.7	84.7	84.3		117.4	113.9	
129	320.9	31.9	13	10.9	13.0		17.9	3.1	103.3	84.0	84.0		125.8	150.0	
130	187.9	18.7	9	12.2			12.2	3.2	103.3	85.0			135.0		
131	229.2	22.6	9	13.2			13.2	3.5	103.6	84.0			154.3		

TABLE 23. 6-in. column, 1/2-in. orifice

Material: Rice-2

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h_2	h_3	h_4	$h_{av.}$	$\frac{hD_p}{K_g}$	T_a	T_{w2}	T_{w3}	T_{w4}	Q_2	Q_3	Q_4
132	573.0	99.1	18	14.3	15.6	19.0	16.6	7.7	117.3	91.2	91.0	91.0	177.2	195.0	326.8
133	687.6	118.9	18	14.5	16.0	15.7	16.4	7.6	114.0	89.3	89.3	89.0	170.0	187.7	306.7
134	181.3	83.3	13	16.1	18.2	.	17.2	7.9	118.7	91.3	91.3		209.5	236.8	
135	573.0	99.1	13	17.0	18.3		17.2	7.4	116.0	89.3	89.3		220.5	237.4	

TABLE 29. 6-in. column, 1/2-in. orifice

Material: Millet

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h_2	h_3	h_L	$h_{av.}$	$\frac{h D_p^2}{K G}$	T_a	T_{w2}	T_{w3}	T_{wL}	Q_2	Q_3	Q_L
136	458.4	70.1	18	12.9	13.3	16.5	14.7	6.0	117.3	91.0	90.7	90.7	161.1	174.4	287.4
137	573.0	87.7	18	11.6	13.3	16.4	13.6	5.5	114.3	90.7	90.0	90.0	130.0	159.3	261.1
138	385.0	58.9	13	15.5	17.0		16.3	6.6	119.0	91.0	91.0		206.2	226.1	
139	458.4	10.2	13	15.1	16.9		16.0	6.5	117.3	92.4	92.0		173.6	203.1	
140	314.0	48.1	9	17.2			17.2	7.0	110.3	90.0			165.9		
141	458.4	70.2	9	17.8			17.8	7.3	111.3	91.3			169.1		

TABLE 30. 6-in. column, 1/2-in. orifice

Material: Timothy

Run No.	G	$\frac{D_p}{\mu}$	Ded height in	h ₂	h ₃	h ₄	h _{av.}	$\frac{hD_p}{K_g}$	T _a	T _{w2}	T _{w3}	T _{w4}	Q ₂	Q ₃	Q ₄
142	160.2	10.9	18	5.8	7.0	10.0	7.6	1.4	105.0	81.3	81.3	82.0	65.3	78.8	150.7
143	206.3	14.0	18	5.4	6.6	10.1	7.4	1.3	102.0	80.3	79.7	79.3	55.7	72.0	150.2
144	126.0	8.6	13	6.9	10.0		8.4	1.5	107.0	82.7	82.7		79.6	115.4	
145	206.3	14.0	13	7.3	10.3		8.8	1.6	106.3	81.7	81.3		84.8	122.4	
146	103.0	7.0	9	9.0			9.0	1.6	107.7	82.7			103.9		
147	160.4	10.9	9	8.9			8.9	1.6	104.0	83.3			87.5		

TABLE 31. 6-in. column, 1/2-in. orifice

Material: Sand

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h_2	h_3	h_4	$h_{av.}$	$\frac{h D_p}{K g}$	T_a	T_{w2}	T_{w3}	T_{w4}	Q_2	Q_3	Q_4
148	195.0	11.8	18	5.1	8.4	14.0	9.2	1.5	110.0	81.7	81.7	81.7	68.5	112.9	259.6
149	252.1	15.3	18	5.0	8.6	14.6	9.4	1.5	112.3	81.3	81.3	81.0	73.7	117.8	299.3
150	151.0	9.2	13	5.9	10.1		8.0	1.3	113.3	78.7	78.7		97.0	166.0	
151	229.2	13.9	13	6.3	11.0		8.7	1.4	119.0	77.0	77.3		125.7	217.9	
152	137.5	8.4	9	6.8			6.8	1.1	112.3	75.7			118.3		
153	206.3	12.5	9	5.9			5.9	1.0	116.3	76.0			112.9		

TABLES 32 - 35

Heat transfer data from a 6-in. column,
9-in., 13-in. and 18-in. bed heights
and 3/8-in. orifice

TABLE 32. 6-in. column, 3/8" orifice

Material: Polyethylene-1

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h_2	h_3	h_4	$h_{av.}$	$\frac{hD_p}{K_g}$	T_a	T_w2	T_w3	T_w4	Q_2	Q_3	Q_4
154	676.1	176.4	18	18.7	20.5	22.6	20.6	14.5	110.3	88.5	88.5	88.0	193.7	212.4	330.2
155	710.5	187.5	18	19.0	21.3	23.0	21.3	15.0	125.4	90.3	90.0	90.0	316.7	358.3	533.3
156	568.4	150.0	13	21.6	22.3		21.9	15.4	105.5	80.0	80.0		261.6	270.1	
157	687.6	181.4	13	20.8	22.3		21.6	15.2	112.0	84.5	84.0		271.6	296.6	
158	424.0	112.0	9	24.3			24.3	17.1	120.3	82.4			437.4		
159	573.0	151.0	9	23.5			23.5	16.5	120.3	82.0			427.5		

TABLE 33. 6-in. column, 3/8" orifice

Material: Wheat-1

Run No.	G	$\frac{DpG}{\mu}$	Bed height in inch	h_2	h_3	h_4	$h_{av.}$	$\frac{hDp}{Kg}$	T_a	TW_2	TW_3	TW_4	Q_2	Q_3	Q_4
160	802.2	234.3	13	16.1	18.8	21.7	18.9	14.7	124.7	90.7	90.3	90.3	260.0	307.2	425.8
161	916.8	267.7	18	16.6	19.5	21.5	19.2	14.9	126.0	91.0	91.0	91.3	276.1	324.3	488.7
162	710.5	207.5	13	20.8	22.5		21.7	16.9	120.0	93.5	93.0		261.8	288.7	
163	779.3	227.6	13	18.8	22.5		20.7	16.1	119.0	92.3	92.3		230.4	285.3	
164	536.3	156.6	9	23.2			23.2	18.1	130.0	94.3			393.4		
165	687.6	200.8	9	23.0			23.0	17.9	132.0	93.7			418.4		

TABLE 34. 6-in. column, 3/8" orifice

Material: Wheat-3

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h ₂	h ₃	h ₄	h _{av.}	$\frac{h D_p}{K_g}$	T _a	T _{w2}	T _{w3}	T _{w4}	Q ₂	Q ₃	Q ₄
166	332.3	46.6	13	10.8	11.6	13.7	12.0	4.5	105.5	84.5	84.5	84.5	107.7	115.7	188.4
167	275.0	38.6	13	11.5	15.3		13.4	4.8	120.0	91.3	91.0		156.8	210.8	
168	194.8	27.3	9	15.5			15.5	5.6	110.3	90.0			149.5		

TABLE 35. 6-in. column, 3/8" orifice

Material: Wheat-4

n	G	$\frac{D_p G}{\mu}$	Bed height in	h ₂	h ₃	h ₄	h _{av.}	$\frac{h_{Dp}}{K_g}$	T _a	T _{w2}	T _{w3}	T _{w4}	Q ₂	Q ₃	Q ₄
9	240.7	23.8	18	8.7	10.5	12.5	10.6	2.8	110.0	83.3	83.3	83.3	110.3	133.1	218.6
10	133.4	12.2	13	10.0	13.0		11.5	3.0	115.5	86.3	86.0		138.7	182.2	
11	155.9	15.5	9	12.9			12.9	3.4	112.3	85.3			177.8-		

TABLES 36 - 39

Heat transfer data for a 3-in. column,
10-in. and 16-in. bed heights
and 1/4-in. orifice

TABLE 36. 3-in. column, 1/4" orifice

Material: Wheat-3

Run No.	G	$\frac{DpG}{\mu}$	Bed height in <u>inch</u>	b ₂	h ₃	$h_{av.}$	$\frac{hDp}{Kg}$	T _a	Tw ₂	Tw ₃	Q ₂	Q ₃
172	531.5	74.5	10	15.2		15.2	5.7	108.0	84.7		139.2	
173	641.3	90.0	10	14.9		14.9	5.6	110.0	89.0		123.0	

TABLE 37. 3-in. column, 1/4" orifice

Material: Wheat-4

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h ₂	h ₃	h _{av.}	$\frac{h D_p}{K_g}$	T _a	T _{w2}	T _{w3}	Q ₂	Q ₃
174	366.6	36.3	16	11.5	13.3	12.4	3.3	100.0	81.3	81.0	84.5	99.3
175	531.5	52.8	16	11.3	14.0	12.7	3.4	110.0	89.0	89.5	93.3	112.8

TABLE 38. 3-in. column, 1/4" orifice

Material: Timothy

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h_2	h_3	$h_{av.}$	$\frac{h D_p}{K_g}$	T_a	TW_2	TW_3	Q_2	Q_3
176	233.0	16.2	16	7.7	10.0	8.9	1.6	84.3	76.7	76.7	23.0	29.9
177	192.0	13.1	16	7.0	11.0	9.0	1.6	85.0	79.7	79.7	14.6	22.9

TABLE 39. 3-in. column, 1/4" orifice

Material: Sand

Run No.	G	$\frac{D_p G}{\mu}$	Bed height in inch	h_2	h_3	$h_{av.}$	$\frac{h D_p}{K g}$	T_a	T_{w2}	T_{w3}	Q_2	Q_3
178	257.0	15.6	10	10.5		10.5	1.7	88.7	78.5		42.1	
179	366.5	22.3	10	10.7		10.7	1.7	92.0	81.3		45.0	

TABLES 40 - 42

Heat Transfer Data for Fluidized Beds From
a 6-in. Column and 5-in. Bed Height

TABLE 40. Fluidized Bed
6-in. column, 5-in. bed height

Material: Wheat-1

Run No.	G	D _p G/μ	h	hD _p /kg	T _a	T _w	Q
180	637.6	200.8	11.1	8.6	141.9	95.7	243.6
181	916.8	267.7	17.7	13.8	167.5	106.3	514.5
182	960.0	280.3	21.2	16.5	140.3	105.0	556.9
183	1031.4	301.2	24.0	18.7	163.0	108.3	680.6
184	1077.2	314.6	24.7	19.2	167.5	106.0	721.5
185	1146.0	334.7	24.8	19.3	163.0	113.7	580.8

TABLE 41. Fluidized Bed
6-in. column, 5-in. bed height

Material: Wheat-3

Run No.	G	D_{pC}/μ	h	hD_p/Kg	T_a	T_w	Q
186	573.0	30.4	23.8	8.9	143.0	108.3	392.2
187	618.3	36.8	26.8	10.0	143.7	108.3	450.8
188	687.6	96.5	28.4	10.6	144.3	111.0	449.3
189	802.2	112.6	28.0	10.5	147.0	113.3	448.3

TABLE 12. Fluidized Bed

6-in. column, 5-in. bed height

Material: Wheat-4

Run No.	G	$D_p G/\mu$	h	$h D_p/K_g$	T_a	T_w	Q
190	389.6	38.7	22.8	6.0	132.7	98.7	368.2
191	412.6	41.0	26.5	7.0	140.3	102.3	478.3
192	435.5	43.2	28.6	7.6	135.3	108.0	370.9
193	458.4	45.5	29.6	7.8	136.0	105.3	431.6
194	504.2	50.1	30.3	8.0	133.3	102.0	450.6
195	573.0	56.9	30.2	8.0	136.0	104.0	459.0

TABLES 43 - 50

Temperature data for the measurement of
thermal conductivity and specific heat

TABLE 43.

Temperature distribution across the cylinder at different points

Material: wheat

$Q = 19.258 \text{ BTU/hr.}$

Time		Thermocouple No.							
Hr.	Min.	1	2	3	4	5	6	7	8
		Temperature °F							
0	00	73.0	73.4	73.0	73.0	73.0	73.5	73.0	73.0
0	15	102.0	76.0	73.0	73.2	73.0	73.5	73.0	73.0
0	30	112.3	81.3	76.0	73.2	73.0	73.5	73.0	73.0
0	45	117.4	85.2	76.0	73.2	73.0	73.5	73.0	73.0
1	00	121.0	88.3	76.0	73.2	73.0	73.5	73.0	73.0
1	30	125.0	92.7	81.3	76.7	74.3	73.5	73.0	73.0
2	00	131.0	96.0	84.7	79.0	75.3	73.5	73.0	73.0
3	00	138.0	102.0	88.3	82.0	78.0	75.3	73.0	73.0
4	00	143.0	105.4	91.6	84.8	81.0	78.0	73.0	73.0
5	00	147.7	109.0	94.3	87.7	82.3	79.0	74.3	73.0
6	00	149.8	111.8	97.0	89.7	84.0	79.7	75.0	73.0
8	00	153.7	115.5	100.3	91.7	86.0	81.3	75.5	73.0
10	00	155.7	117.3	102.0	93.5	87.5	82.8	75.6	73.0
12	00	157.0	118.3	103.0	95.0	88.3	83.0	76.0	73.0
16	00	156.6	120.0	104.3	95.6	89.8	84.4	76.0	73.0
18	00	156.7	120.0	104.0	95.6	90.0	84.5	76.0	73.0
20	00	156.7	119.6	103.8	95.6	90.0	84.5	76.0	73.0
24	00	156.7	119.6	103.8	95.6	90.0	84.5	76.0	73.0
28	00	156.7	119.6	103.8	95.6	90.0	84.5	76.0	73.0

TABLE 44.

Temperature distribution across the cylinder at different points

Material: polyethylene (small size)

Q = 12.325 BTU/hr.

Time		Thermocouple No.							
		1	2	3	4	5	6	7	8
Hr.	Min.	Temperature °F							
0	00	72.0	72.0	72.3	72.4	72.3	72.0	72.0	72.0
0	30	91.7	72.0	72.3	72.4	72.3	72.0	72.0	72.0
1	00	98.0	79.6	72.3	72.4	72.3	72.0	72.0	72.0
2	00	103.7	85.7	73.0	74.4	72.3	72.0	72.0	72.0
3	00	107.4	89.0	81.4	78.0	75.3	73.0	72.0	72.0
4	00	110.7	91.7	83.3	80.0	77.0	75.4	72.0	72.0
5	00	112.0	93.3	85.4	81.3	79.0	76.5	74.7	72.0
6	00	114.0	95.0	87.0	82.5	80.0	77.0	75.0	72.0
8	00	115.7	97.4	89.0	84.5	81.3	78.7	75.0	72.0
10	00	117.0	98.7	90.0	85.3	82.5	79.7	76.0	72.0
12	00	119.0	100.3	91.7	86.5	83.0	80.3	76.0	72.0
14	00	121.0	101.3	92.0	87.5	84.0	81.0	76.0	72.0
16	00	121.0	102.0	92.6	88.3	84.7	81.3	76.0	72.0
18	00	121.0	102.0	93.0	88.3	84.7	81.3	76.0	72.0
20	00	121.0	102.0	93.0	88.3	84.7	81.3	76.0	72.0
24	00	121.0	102.0	93.0	88.3	84.8	81.3	76.0	72.0

TABLE 45.

Temperature distribution across the cylinder at different points

Material: Millet

Q = 400

Time		Thermocouple No.							
		1	2	3	4	5	6	7	8
Hr.	Min.	Temperature °F							
0	00	74.0	74.0	74.5	74.3	74.3	74.0	74.0	74.0
0	30	107.3	82.0	74.5	74.3	74.3	74.0	74.0	74.0
1	00	114.0	86.5	79.0	76.0	74.3	74.0	74.0	74.0
2	00	122.7	93.3	83.0	79.0	76.0	75.0	74.0	74.0
3	00	128.4	97.7	87.4	82.6	78.7	76.0	74.0	74.0
4	00	131.0	100.3	89.6	84.6	80.5	78.0	75.3	74.0
5	00	135.4	102.0	91.0	86.0	81.4	78.7	76.3	74.0
6	00	136.7	104.0	92.7	87.0	83.0	79.4	78.0	74.0
7	00	139.0	105.5	94.0	88.5	83.7	80.0	78.5	74.0
8	00	139.7	107.0	95.0	89.0	84.7	80.3	79.3	74.0
10	00	140.0	108.0	96.5	90.0	85.0	81.3	79.6	74.0
12	00	140.0	109.0	97.0	90.8	85.7	81.3	79.7	74.0
14	00	140.0	109.3	97.3	91.0	86.0	81.3	79.7	74.0
16	00	140.0	109.7	97.7	91.3	86.5	81.9	79.3	74.0
18	00	140.0	110.3	98.0	91.7	87.0	81.9	79.3	74.0
20	00	140.0	110.3	98.0	91.7	87.0	81.9	79.3	74.0

TABLE 46.
Temperature distribution across the cylinder at different points

Material: Rice

Q = 19.258 BTU/hr.

Time		Thermocouple No.							
		1	2	3	4	5	6	7	8
Hr.	Min.	Temperature °F							
0	00	73.0	73.4	73.0	73.4	73.5	73.0	73.0	73.0
0	15	107.3	78.0	73.0	73.4	73.5	73.0	73.0	73.0
0	30	115.7	84.0	73.0	73.4	73.5	73.0	73.0	73.0
0	48	121.0	88.3	80.7	73.4	73.5	73.0	73.0	73.0
1	00	121.3	91.0	82.7	78.0	73.5	73.0	73.0	73.0
1	30	129.3	95.0	85.4	79.0	79.0	76.7	73.0	73.0
2	00	131.7	98.0	87.3	80.4	79.5	77.0	73.0	73.0
2	30	134.0	100.3	89.3	82.0	81.3	78.0	73.0	73.0
3	00	136.0	102.0	90.7	83.3	82.0	80.7	73.0	73.0
4	00	140.7	105.3	93.3	85.7	83.7	80.7	73.0	73.0
5	00	142.3	108.0	96.5	88.4	85.0	81.4	73.0	73.0
7	00	148.0	111.3	99.0	90.7	87.3	83.0	73.0	73.0
10	00	153.0	115.7	102.0	93.0	89.0	84.3	73.0	73.0
16	00	156.3	119.0	105.3	95.7	90.7	86.0	73.0	73.0
20	00	154.7	120.0	105.0	97.0	90.0	86.5	73.0	73.0
24	00	155.3	121.0	105.3	97.7	91.7	86.5	83.3	73.0
28	00	155.3	121.0	105.3	97.7	91.7	86.5	83.3	73.0
30	00	155.3	121.0	105.3	97.7	91.7	86.5	83.3	73.0

TABLE 47.

Temperature distribution across the cylinder at different points

Material: Timothy

Q = 19.258 BTU/hr.

Time		Thermocouple No.							
		1	2	3	4	5	6	7	8
hr.	Min.	Temperature °F							
0	00	71.5	71.0	71.2	71.3	71.3	71.0	71.0	71.0
0	15	105.4	71.0	71.2	71.3	71.3	71.0	71.0	71.0
0	30	115.8	79.0	71.2	71.3	71.3	71.0	71.0	71.0
1	00	127.7	83.3	75.0	71.3	71.3	71.0	71.0	71.0
2	00	141.3	99.3	83.0	76.4	71.3	71.0	71.0	71.0
3	00	153.0	105.4	88.4	81.5	76.0	71.0	71.0	71.0
4	00	160.0	110.7	93.0	84.8	79.4	75.0	71.0	71.0
6	00	168.0	118.3	99.4	91.0	83.3	78.0	71.0	71.0
8	00	171.4	121.7	103.0	94.0	86.5	81.0	71.0	71.0
10	00	174.3	123.7	104.7	95.0	88.0	81.3	71.0	71.0
12	00	176.7	126.5	105.3	96.0	89.0	81.3	71.0	71.0
20	00	180.0	130.0	109.0	99.7	90.8	83.0	78.7	71.0
32	00	186.3	134.5	112.0	100.7	91.7	83.3	79.7	71.0
36	00	188.0	136.0	112.0	101.3	91.7	83.3	79.7	71.0
40	00	188.0	136.0	112.0	101.3	91.7	83.3	79.7	71.0

TABLE 48.

Temperature distribution across the cylinder at different points

Material: Sunflower

$Q = 19.258 \text{ BTU/hr.}$

Time		Thermocouple No.							
		1	2	3	4	5	6	7	8
Hr.	Min.	Temperature °F							
0	00	73.0	73.4	73.2	73.0	73.5	73.0	73.0	73.0
0	15	128.3	81.3	73.2	73.0	73.5	73.0	73.0	73.0
0	30	144.7	91.8	76.0	73.0	73.5	73.0	73.0	73.0
0	45	153.0	92.0	80.7	74.4	73.5	73.0	73.0	73.0
1	00	155.3	102.0	83.7	76.7	73.5	73.0	73.0	73.0
1	30	166.3	109.0	89.0	81.3	76.0	73.0	73.0	73.0
2	00	171.3	114.0	93.0	84.7	82.0	78.0	73.0	73.0
3	00	178.3	121.4	99.3	90.0	84.0	80.0	75.0	73.0
4	00	185.0	126.0	103.4	93.3	86.5	81.3	77.0	73.0
6	00	191.3	132.8	109.0	98.0	90.3	84.7	80.0	73.0
8	00	195.3	136.7	112.0	100.0	92.0	85.8	81.3	73.0
10	00	196.3	139.6	113.5	102.0	93.3	86.5	81.3	73.0
12	00	196.3	140.3	114.3	102.0	94.4	87.0	81.3	73.0
14	00	196.3	140.8	115.0	103.0	94.5	87.5	81.3	73.0
16	00	196.3	140.8	115.5	103.0	94.5	87.9	81.3	73.0
20	00	196.3	140.8	115.5	103.0	94.5	87.9	81.3	73.0
24	00	196.3	140.8	115.5	103.0	94.5	87.9	81.3	73.0

TABLE 19.

Temperature distribution across the cylinder at different points

Material: Flax seeds

$Q = 19.258 \text{ BTU/hr.}$

Time		Thermocouple No.							
		1	2	3	4	5	6	7	8
Hr.	Min.	Temperature °F							
0	00	72.0	72.0	72.5	72.3	72.0	72.3	72.0	72.7
0	15	105.3	72.0	72.5	72.3	72.0	72.3	72.0	72.7
0	30	117.3	79.7	73.0	72.3	72.0	72.3	72.0	72.7
1	00	126.7	86.5	77.0	73.3	72.0	72.3	72.0	72.7
2	00	136.0	94.0	83.3	78.0	74.3	72.3	72.0	72.7
3	00	144.0	100.3	88.3	81.3	78.0	75.3	75.9	72.7
4	00	147.0	103.7	91.7	84.7	80.3	78.0	75.7	72.7
5	00	151.7	107.3	94.3	87.7	82.7	79.3	78.0	72.7
6	00	154.3	110.3	97.7	89.7	84.0	80.3	79.0	72.7
8	00	157.7	114.3	100.0	92.0	86.0	82.0	80.3	72.7
10	00	161.3	116.4	102.7	93.7	87.7	82.6	80.3	72.7
12	00	165.3	118.3	103.7	94.3	88.3	82.7	79.3	72.7
16	00	167.3	120.3	105.3	96.0	89.7	84.0	81.3	72.7
20	00	168.3	121.4	107.0	97.0	90.8	84.9	81.3	72.7
24	00	169.0	121.4	107.3	97.5	90.8	84.9	81.3	72.7
28	00	169.0	121.4	107.3	97.5	90.8	84.9	81.3	72.7

TABLE 50.

Temperature distribution across the cylinder at different points

Material: corn

Q = 19.258 BTU/hr.

Time		Thermocouple No.							
Hr.	Min.	1	2	3	4	5	6	7	8
		Temperature °F							
0	00	72.5	73.0	75.2	73.0	73.0	73.4	73.3	73.0
0	15	105.0	73.0	73.2	73.0	73.0	73.4	73.3	73.0
0	30	117.4	73.3	73.2	73.0	73.0	73.4	73.3	73.0
1	00	127.0	86.5	73.3	73.0	73.0	73.4	73.3	73.0
1	30	132.5	92.3	80.0	73.0	73.0	73.4	73.3	73.0
2	00	137.3	97.0	93.0	76.4	73.0	73.4	73.3	73.0
3	00	143.0	102.0	89.0	81.0	76.0	73.4	73.3	73.0
4	00	148.0	106.5	91.4	84.8	79.3	76.0	73.3	73.0
5	00	152.6	109.0	95.0	87.0	81.3	73.0	73.3	73.0
8	00	158.0	115.9	103.3	91.7	85.3	81.0	73.3	73.0
10	00	161.3	119.0	103.0	94.5	87.7	82.7	79.3	73.0
12	00	161.7	120.7	104.5	95.8	89.0	83.7	80.0	73.0
16	00	164.0	122.7	106.0	97.0	90.0	84.6	80.4	73.0
20	00	164.4	123.3	107.0	98.0	90.7	84.8	81.3	73.0
24	00	166.3	123.5	107.0	98.0	90.7	84.3	81.3	73.0
28	00	166.3	123.5	107.0	98.0	90.7	84.8	81.3	73.0

TABLE 51.

Constants for Bessel Functions

Materials	A ₁	A ₂	A ₃	A ₄	A ₅	A ₆	A ₇	A ₈	A ₉	A ₁₀
Wheat	33.4290	14.7544	9.4464	6.9250	5.4867	4.5227	3.8652	3.3551	2.9839	2.6692
Corn	37.1625	16.4033	10.4930	7.7002	6.0937	5.0297	4.2923	3.7316	3.3132	2.9691
Polyethylene (small)	18.2461	8.0482	5.1531	3.7774	2.9931	2.4670	2.1036	1.8391	1.6278	1.4560
Flax Seed	34.2775	15.1262	9.6792	7.1993	5.6214	4.6376	3.9598	3.4406	3.0567	2.7374
Millet	25.9432	11.4653	7.3220	5.3240	4.2509	3.5177	2.9936	2.6109	2.3103	2.0773
Rice	31.7281	14.0095	8.9574	6.5772	5.2015	4.2965	3.6636	3.1878	2.8278	2.5365
Timothy	48.0310	20.8929	13.6309	9.7679	7.9428	6.3607	5.6100	4.7068	4.3404	3.7365

TABLE 52.
Spout diameter data from 6 inch semicircular column with
0.50 inch orifice and 12 inch bed height

Material	Mass velocity lb/(hr.)(sq.ft.)	Spout diameter d_s inches								Average d_s inches
		Bed level from the orifice in inches								
		1	2	4	6	8	10	11		
Wheat	704.0	1.30	1.31	1.31	1.40	1.43	1.50	1.50	1.39	
	776.0	1.30	1.38	1.40	1.51	1.51	1.51	1.53	1.45	
	845.4	1.38	1.50	1.51	1.51	1.51	1.53	1.56	1.50	
Rice	535.2	1.10	1.13	1.14	1.14	1.14	1.13	1.13	1.13	
	594.0	1.19	1.22	1.31	1.31	1.31	1.25	1.31	1.27	
	654.0	1.19	1.31	1.37	1.38	1.38	1.34	1.37	1.33	

TABLE 53. Data on Spout Diameter

Material	Column diameter inches d_c	Orifice diameter inches d_o	Bed height inches L	Mass velocity lb/(hr)(sq.ft.) G	Average spout diameter d_s	Mean deviation from average d_s
Polystyrene 1	6	0.50	12	326.0	1.13	0.05
				356.2	1.20	0.05
				416.3	1.27	0.05
				476.1	1.33	0.05
			8	259.5	1.07	0.05
				296.4	1.13	0.04
				355.8	1.16	0.03
	4	0.50	6	320.2	0.72	0.01
				373.6	0.80	0.01
				453.6	0.85	0.01
		0.25	12	593.9	1.06	0.00
				667.2	1.12	0.00
Polystyrene 2	6	0.50	12	595.0	1.47	0.07
				654.0	1.52	0.08
				713.8	1.58	0.05
			8	506.0	1.38	0.03
				536.2	1.40	0.03
				594.8	1.50	0.06
	4	0.50	6	762.7	1.10	0.03
				890.0	1.20	0.03
Barley	6	0.50	12	635.0	1.35	0.09
				705.0	1.47	0.09
				775.4	1.49	0.05
			8	528.4	1.31	0.02
				563.6	1.35	0.04
				634.0	1.44	0.08

TABLE 53 (continued)

Material	Column diameter inches d_c	Orifice diameter inches d_o	Bed height inches L	Mass velocity $lb/(hr)(sq.ft.)$ G	Average Spout diameter d_s	Mean deviation from average d_s
Polyethylene	6	0.50	12	512.0	1.37	0.07
				530.0	1.43	0.06
				619.0	1.50	0.07
				706.0	1.62	0.07
				795.0	1.68	0.05
				883.6	1.75	0.07
Millet	6	0.50	8	442.0	1.23	0.07
				486.0	1.34	0.04
				530.0	1.37	0.05
				573.6	1.50	0.05
				618.2	1.50	0.06
			12	386.2	1.02	0.02
				416.0	1.10	0.08
				475.6	1.16	0.02
				535.2	1.25	0.06
				594.0	1.28	0.04
4	0.50	6	326.0	1.00	0.00	
			356.4	1.05	0.03	
			416.0	1.10	0.04	
			475.6	1.14	0.04	

TABLE 53 (continued)

Material	Column diameter inches d_c	Orifice diameter inches d_o	Bed height inches L	Mass velocity lb/(hr)(sq.ft.) G	Average spout diameter d_s	Mean deviation from average d_s	
Wheat	6	0.50	12	704.0	1.39	0.07	
				776.0	1.45	0.08	
				845.4	1.50	0.03	
				8	563.6	1.35	0.04
				634.2	1.42	0.08	
				704.0	1.45	0.08	
		0.25	12	795.9	1.47	0.09	
			884.3	1.53	0.05		
			8	663.4	1.34	0.09	
				707.5	1.44	0.09	
				795.9	1.53	0.05	
	4	0.625	10	954.8	1.12	0.00	
			1028.2	1.25	0.03		
			1175.1	1.28	0.04		
	0.50	6	889.0	1.00	0.02		
		1017.0	1.12	0.03			
		1193.5	1.20	0.03			
			1273.3	1.20	0.04		
	0.25	8	881.3	1.19	0.00		
		1028.2	1.22	0.03			
		1175.1	1.31	0.00			
		10					
			999.2	1.24	0.01		
			1175.1	1.31	0.01		

TABLE 53 (continued)

Material	Column diameter inches d_c	Orifice diameter inches d_o	Bed height inches L	Mass velocity lb/(hr)(sq.ft.) G	Average spout diameter d_s	Mean deviation from average d_s
Wheat	6 ^a	0.75	24	1054.0	1.63	0.09
				1160.0	1.70	0.05
				1265.0	1.75	0.05
	24 ^a	4.00	72	736.3	3.25	0.20
				638.9	3.13	0.23
				593.1	3.13	0.23
	60			604.6	2.95	0.25
				664.6	3.18	0.18
				724.8	3.53	0.18
	36			428.0	2.53	0.08
Rice	6	0.50	12	462.0	2.69	0.13
				541.4	2.80	0.20
				535.2	1.13	0.01
	8			594.0	1.27	0.04
				654.0	1.33	0.05
				416.1	1.06	0.06
	4	0.50	6	476.0	1.11	0.01
				535.8	1.25	0.03
				663.0	0.94	0.03
				928.6	1.10	0.04

TABLE 53 (continued)

Material	Column diameter inches d_c	Orifice diameter inches d_o	Bed height inches L	Mass velocity lb/(hr)(sq.ft.) G	Average spout diameter d_s	Mean deviation from average d_s
Rice	4	0.25	10	800.6	1.14	0.03
				934.1	1.28	0.06
				1067.5	1.33	0.08
Corn	6	0.50	8	694.1	1.04	0.05
				934.1	1.17	0.05
				1067.5	1.28	0.08
			12	1195.2	2.12	0.14
				1326.6	2.28	0.12
				840.0	1.75	0.05
Flax seeds	6	0.50	8	972.0	1.98	0.04
				356.4	1.08	0.05
				416.0	1.17	0.08
			12	426.9	0.73	0.04
				453.9	0.80	0.03
				624.4	0.90	0.03

TABLE 54

Values of x for which $J_0(x) = 0$, and
corresponding values of $J_1(x)$

<u>Value of x for which $J_0(x) = 0$</u>	<u>Corresponding value of $J_1(x)$</u>
2.4048	+ 0.5191
5.5201	- 0.3403
8.6537	+ 0.2715
11.7915	- 0.2325
14.9309	+ 0.2065
18.0711	- 0.1877
21.2116	+ 0.1732
24.3525	- 0.1617
27.4935	+ 0.1521
30.6346	- 0.1441